Autonomy Reshapes How Personalization Affects Privacy Concerns and Trust in LLM Agents

Zhiping Zhang[1*] **Yi Evie Zhang**[4] **Freda Shi**[2,3] **Tianshi Li**[1]
[1]Northeastern University [2]University of Waterloo [3]Vector Institute
[4]University of Illinois Urbana-Champaign
{zhang.zhip,tia.li}@northeastern.edu yiz28@illinois.edu fhs@uwaterloo.ca

Abstract

LLM agents require personal information for personalization in order to effectively act on users' behalf, but this raises privacy concerns that can discourage data sharing, limiting both the autonomy levels at which agents can operate and the effectiveness of personalization. Yet the expanded design space of agent autonomy also presents opportunities to shape these effects, which remain underexplored. We conducted a 3×3 between-subjects experiment ($N = 450$) to study how agent autonomy level influences personalization's effects on users' privacy concerns, trust, and willingness to use, as well as the underlying psychological processes. We find that risk-contingent autonomy, where the agent delegates control back to users upon detecting potential privacy leakage, improves users' perceived control. This in turn attenuates personalization's adverse effects: privacy concerns rise less and trust declines less. Our results suggest that designing **agent's autonomy** that supports **human autonomy** (both perceived control and oversight effectiveness) helps users benefit from personalization without being deterred by growing privacy concerns. This positions aligning decision authority between users and agents (**autonomy alignment**) as an important opportunity and challenge for trustworthy human-agent interaction.

1 Introduction

Large Language Model (LLM) agents such as OpenClaw (OpenClaw, 2025), OpenAI's Operator (OpenAI, 2025b), and Claude Code (Anthropic, 2026) operate with higher levels of autonomy than non-agentic AI systems, completing tasks under limited human instruction. Here, autonomy refers to the degree to which an agent can operate independently of humans (Kasirzadeh & Gabriel, 2025). To perform tasks on behalf of users effectively, LLM agents require access to users' personal data for personalization. A common practice is connecting agents to external applications (OpenClaw, 2025; Meta, 2026) such as Gmail and Notion, where up-to-date personal data can be accessed and used to personalize agent behavior (Zhang et al., 2024a).

However, unlike non-agentic AI systems that only generate static content to populate a fixed, predefined interface, LLM agents plan and execute actions on the fly, such as generating and sending messages to specific recipients through real-world tools (Muthusamy et al., 2023; Talebirad & Nadiri, 2023). Through interactions with the external environment, there is a risk that agents may expose users' data (Shao et al., 2024; Mireshghallah et al., 2023). The more personal data an agent accesses for personalization, the greater the risk could be, which in turn raises users' privacy concerns, reduces trust and users' willingness of data sharing (Awad & Krishnan, 2006; Aguirre et al., 2016; Wang et al., 2024). For example, recent studies found that users worry agents might share sensitive information in social interaction scenarios in ways that conflict with their privacy preferences (Goyal et al., 2024; Zhang et al., 2024b). These negative perceptions represent a critical barrier to the adoption of personalized LLM agents and the development of trustworthy agentic AI applications.

*This work was started when the author was a visiting student at the University of Waterloo.



Figure 1: Overview of the 3×3 experimental conditions. **Personalization type varies what user information the agent can access to generate responses**: (1) Full personalization (the agent has full access to all user information in the connected applications); (2) Privacy-aware personalization (the agent has access to only non-sensitive user information); (3) No personalization (the agent has no access to any user information). **Autonomy level varies the agent's independence in executing actions** (e.g., acting on the user's behalf in a group discussion as an example): (1) No autonomy (the agent always requires user confirmation before sending responses); (2) Risk-contingent autonomy (the agent turns to the user for confirmation when potential sensitive information is detected); (3) Full autonomy (the agent handles the task fully autonomously).

Despite current technical approaches to mitigating privacy and security risks in LLM agents, such as red-teaming (Nie et al., 2024; He et al., 2025) and model alignment (Zhou et al., 2025; Sun & Zhao, 2024; Zhu et al., 2025), understanding how expanded design space of agent autonomy influences the effects of personalization on users' privacy concerns and trust remains essential to inform the design of trustworthy agents that not only operate safely but also help users benefit from personalization without being deterred by privacy concerns. In this study, we aim to investigate:

RQ1: How does the level of agent autonomy influence the effects of personalization on users' privacy concerns, trust, and willingness to use LLM agents?

RQ2: Through what underlying psychological processes does agent autonomy influence personalization's effects?

To answer these questions, we conducted a controlled 3×3 between-subjects experiment ($N = 450$) in which human participants interacted with an LLM agent acting on their behalf in an interpersonal communication scenario. We manipulated two factors: **autonomy level** of the agent and the **personalization type** as illustrated in Figure 1. Each participant first provided personal information as personalization materials, then was introduced to and used an assigned LLM agent acting on their behalf in the task, and finally completed a post-survey reporting their perceptions of the agent. Our key contributions are as follows:

- A controlled factorial experiment that provides empirical evidence of how the agent's autonomy level influences personalization's effects on users' privacy concern, trust and willingness to use in the LLM agents.
- Evidence that risk-contingent autonomy, where the agent delegates control to the user upon detecting potentially sensitive information, attenuates personalization's adverse effects, reducing the increase in privacy concerns and the decrease in trust. This finding suggests that **configuring proper agent autonomy offers a promising approach to help users benefit from personalization without being deterred by growing privacy concerns**. It positions *autonomy alignment*, aligning decision authority between users and LLM agents, as an important design consideration for human-agent interaction.

- Moderated mediation analysis revealing that **user perceived control** is the key mechanism through which agent autonomy moderates personalization's effects. Counterintuitively, delegating more control to users does not necessarily enhance perceived control. Users using an agent with risk-contingent autonomy reported higher perceived control and were more effective at identifying privacy leakages, even compared to those in the condition where users always had control over the agent's responses. Our results highlight the importance of **designing agent autonomy that supports human autonomy** rather than simply maximizing the amount of user control.

2 Methodology

We designed a 3 (autonomy level) $\times$ 3 (personalization type) between-subjects experiment. Each participant was randomly assigned to one of nine conditions and used the assigned LLM agent, which acted on their behalf in a group discussion (see Section 2.1 for detailed system design). After the task, participants completed a post-task survey measuring their perception of using the LLM agent (see Section 2.2 for the full procedure).

2.1 Study Meterials

2.1.1 Overview of the System

The use of LLM agents in our study is in the context of a group discussion scenarios. We included two representative scenarios to broaden participants' reactions for exploratory purposes: one in a professional work context (a weekly update meeting with colleagues) and one in a personal daily-life context (a family travel plan discussion with relatives)[1].

To ensure experimental control, we built the LLM agent and the group discussion system ourselves . The group discussion system included a chat interface and three agents: one agent that acted on behalf of users, driven by GPT-4o-mini (Appendix A.2.1), and two role-playing agents that simulated other entities in a group discussion (two colleagues in the weekly update meeting scenario, or two relatives in the family travel plan scenario). The responses of the two role-playing agents were largely scripted to ensure consistency across conditions, with some parts generated by GPT-4o-mini based on participants' personal information to enhance the realism of the discussion (see the full scripts in Appendix A.1).

2.1.2 Design and Manipulation of Agent's Autonomy Level

We operationalized the agent's autonomy based on the AI agent autonomy framework (Kasirzadeh & Gabriel, 2025), **which defines autonomy as the degree to which a system can operate independently of humans**. We selected three representative levels from the framework as experimental conditions: two extremes (No Autonomy and Full Autonomy) and one intermediate condition (Risk-Contingent Autonomy).

No Autonomy (baseline): The LLM agent composed a message but always required the participant's explicit approval or edits before sending it.

Full Autonomy: The agent managed the entire conversational flow and sent messages automatically without requiring participant approval. Participants could only observe the discussion but had no opportunity to intervene.

Risk-Contingent Autonomy: Risk-contingent autonomy refers to the intermediate autonomy level in the framework (Kasirzadeh & Gabriel, 2025), which defines it as an agent that *"can perform the majority of tasks independently, though it still relies upon input from the principal for critical determinations"*. In our study, we define critical determinations as situations involving potential privacy violations, reflecting current privacy-preserving design practices in

[1]While we did not intend to systematically examine scenario effects, we treated scenario as a random factor in the mixed-effects models and found no significant effects of scenario on the main outcomes, as detailed in Section 3.1.

which **systems defer to humans when risks are detected** (e.g., AirGapAgent (Bagdasarian et al., 2024) escalates to the user when information outside the approved set is requested; Operator (OpenAI, 2025b) escalates to the user when predefined high-stakes domains are involved.). The LLM agent generated and sent messages automatically by default, while withheld the message and required the participant's approval before sending when potential sensitive information detected (details in Section 2.1.3).

2.1.3 Sensitivity Detection

The sensitivity detection module used an "LLM-as-a-judge" approach (powered by GPT-4o) to identify potentially sensitive information in generated responses, **without any personalization** to avoid confounding with the personalization manipulation. The sensitivity detection followed the approach to evaluate sensitivity of LLM agent action introduced by Shao et al. (2024), **where a separate model (distinct from the one driving the agent) extracted a list of potentially sensitive information in the task context and then judged whether the agent's message included any of these elements**. (see Appendix A.2.2 for detailed prompts). This sensitivity detection module along all the conditions and the sensitive reminder UI was kept consistent across conditions for fair comparison.

2.1.4 Design and Manipulation of Agent's Personalization Type

We manipulated personalization by controlling the amount of user knowledge that the LLM agent could access to generate responses in the discussion task. To simulate market practices where LLM agents access user data from connected third-party applications (OpenAI, 2025a; Anthropic, 2025; OpenClaw, 2025; Meta, 2026), we reformatted participants' personal information from a pre-survey (Appendix A.3.1) into *Notion Note* and *Google Calendar* formats and structured the data in JSON to feed into the LLM agent (Shao et al., 2024). Following prior work, we employed a "personalization via prompting" technique, which involves including specific user information as context within the prompts provided to the agent (Zhang et al., 2024a). Personal information collected in the pre-survey was sent to the LLM agent backend via API and included in the prompts under three conditions:

Full Personalization (baseline): The LLM agent had full access to all provided information of the participant. This condition is to simulate the most common types of personalization in current LLM agents (OpenClaw, 2025; Meta, 2026; Anthropic, 2025), where the agent can access and use all user information from connected applications to generate tailored responses, but it does not account for the user's privacy preferences.

No Personalization: The agent had no access to any participant data, simulating a general-purpose assistant without personalization (Zhang et al., 2024a).

Privacy-Aware Personalization: This condition simulates an ideal case in which the user has pre-specified their privacy boundaries and the agent strictly enforces them, grounded in the conception of *privacy-as-control* (Westin, 2003), under which individuals decide which of their information is disclosed and to whom. Treating each participant as the authority over their own data, we let them mark in the pre-survey (Appendix A.3.1) the information they did not want shared, thereby defining their own data-flow policy: the agent could access only the information outside that boundary, so a user-defined sensitive item could never enter its context or be disclosed. This represents the model-alignment "best case" that most current work pursues (Teku et al., 2025; Wu et al., 2023).

2.2 Study Procedure

The study was conducted **on Qualtrics[2] with integration of our own LLM agent and interaction system.** Each participant completed the study in the following four steps:

Step 1: Providing personal information for personalization. In the pre-survey (Appendix A.3.1), participants provided non-sensitive information required for the assigned discussion scenario and sensitive information that they explicitly indicated they did not

[2]Qualtrics is a website for building online survey study.

want others in the scenario to know. We collected participants' real personal information to ensure authentic reactions and perceptions. This information was then integrated into the agent's knowledge base for personalization during the interaction session.

Step 2: Introduction to the assigned LLM agent condition. Participants were introduced to one of the nine LLM agent conditions, including information on what personal data the agent could access for the task (personalization type), what actions the agent could perform during the discussion, and what controls the participant retained (autonomy level).

Step 3: Using the LLM agent in the task. After confirming that they understood what the agent is and what it can do, participants entered an group discussion session where the LLM agent acted on their behalf. We implemented the study as a text-based chat to avoid confounding effects from multimodal interactions.

Step 4: Reporting perceptions of the LLM agent. In a post-hoc survey (Appendix A.3.2), participants reported their privacy concerns, trust, willingness to use the agent, and factors related to the underlying psychological mechanisms (perceived sensitivity, perceived control, perceived usefulness), other individual differences and demographic information.

2.3 Data Collection

We recruited U.S.-based participants through Prolific[3] and compensated them $2.80 each for a 12-15 minute study. Based on a power analysis (G*Power, $f = 0.25$, 95% power, $\alpha = 0.05$), we aimed for $N = 450$ participants, evenly distributed across nine conditions (50 per condition). After applying exclusion criteria (scenario filter, attention checks, manipulation validation), we retained 450 valid responses from 538 total. Post-hoc validation confirmed the validity of the experimental manipulations (see Appendix A.4.1 for detailed exclusion criteria and validation checks). Demographic details are provided in Appendix A.4.2.

3 Result

3.1 Risk-contingent autonomy attenuates personalization's effects on users' privacy concern, trust and willingness to use LLM agents (RQ1)

We fit three linear mixed-effects models (one per outcome) with autonomy level, personalization type, and their interaction as fixed effects, controlling for individual differences (AI literacy, personal agency, interpersonal agency, age, gender, education). A random intercept for scenario was included but contributed negligibly to explained variance (marginal and conditional R^2 were near-identical), and residual diagnostics revealed no major violations of normality or homoscedasticity. Models were estimated with REML using `lmerTest` and achieved stable convergence. See Appendix A.5.1 for complete results.

Compared to full personalization, both no personalization and privacy-aware personalization were associated with significantly lower privacy concern (No: $\beta = -2.07, p < .001$; Privacy-aware: $\beta = -1.39, p < .001$), higher trust (No: $\beta = 0.97, p < .001$; Privacy-aware: $\beta = 0.88, p < .001$), and higher willingness to use (No: $\beta = 0.97, p < .05$; Privacy-aware: $\beta = 1.10, p < .01$). These results confirm that **personalization without considering user privacy preferences results in higher privacy concerns, lower trust, and lower willingness to use the agent.**

Regarding autonomy, compared to agents with no autonomy, **participants interacting with agents with risk-contingent autonomy reported lower privacy concern** ($\beta = -0.79, p < .05$) **and higher trust** ($\beta = 0.49, p < .05$). However, full autonomy showed no significant effects on any outcome, suggesting that users interacting with no-autonomy and full-autonomy agents experienced comparable levels of three perception outcomes.

Moreover, the interaction effect between personalization and autonomy was significant. As shown in Figure 2, the same general trend held across all autonomy levels: full personalization produced the highest privacy concern, the lowest trust, and the lowest willingness

[3] Prolific is a website for recruiting research study participants.

Table 1: Conditional indirect effects of personalization (vs. full personalization) on outcomes **through user perceived control**, under no autonomy and risk-contingent autonomy. Significant effects (95% CI excludes 0) are in **bold**. A significant effect (row 1 or 2) indicates that personalization influences the outcome through perceived control at that autonomy level; a significant index of moderated mediation (row 3) indicates that risk-contingent autonomy moderates that indirect effect.

	No personalization			Privacy-aware personalization		
	Concern	Trust	Will.	Concern	Trust	Will.
Effects under No Autonomy	**–.32**	**.42**	**.44**	**–.31**	**.42**	**.44**
Effects under Risk-Contingent Autonomy	–.06	.17	.21	–.02	.09	.15
Index of Moderated Mediation	**.26**	**–.25**	**–.23**	**.29**	**–.34**	**–.29**

Notes. Concern = privacy concern; Will. = willingness to use.

to use. However, under risk-contingent autonomy, the slope across personalization types was substantially *flatter* than under no autonomy or full autonomy. This indicates that **risk-contingent autonomy attenuates the effects of personalization on users' perceptions**.



(a) Privacy concern (b) Trust (c) Willingness to use

Figure 2: Interaction effects of personalization type and autonomy level: Points represent estimated marginal means; vertical bars indicate 95% confidence intervals. Under risk-contingent autonomy, the slope across personalization types is flatter, indicating that autonomy attenuates personalization's effects.

3.2 Risk-contingent autonomy attenuates personalization's effects by improving perceived control, and helps users identify privacy leakages in agent's action (RQ2)

To understand why risk-contingent autonomy attenuates personalization's effects, we conducted a moderated mediation analysis using structural equation modeling (SEM) with three mediators: *perceived sensitivity* (whether the user believed the agent disclosed sensitive information), *perceived control* (the user's sense of control over the agent), and *perceived usefulness*, grounded in the Technology Acceptance Model (Marangunić & Granić, 2015) and Privacy Calculus (Dinev & Hart, 2006). Personalization served as the independent variable, and autonomy was modeled as both an independent variable and a moderator of personalization's effects (see Appendix A.6.2). The model fit the data well ($\chi^2(1) = 0.314$, $p = 0.854$; CFI=1.000; SRMR=0.001; RMSEA=0.000; complete results in Appendix A.6.3).

Risk-contingent autonomy attenuates personalization's effects through improving user perceived control. Under no autonomy, both no personalization and privacy-aware personalization significantly increased perceived control compared to full personalization ($a_{2\text{no}} = 0.67, p < .01$; $a_{2\text{privacy-aware}} = 0.66, p < .01$), which in turn reduced privacy concern ($b_2 = -0.48, p < .001$) and increased trust ($b_2 = 0.42, p < .001$) and willingness ($b_2 = 0.44, p < .001$). The indirect effects through perceived control were significant for

Table 2: Effects of risk-contingent autonomy (IA) (compared to no autonomy) on mediators (M) and indirect paths to outcomes. Significant effects (95% CI excludes 0) in **bold**. Only perceived control shows significant effects across all paths, indicating that risk-contingent autonomy influences outcomes exclusively through improving perceived control.

	$IA \rightarrow M$	$IA \rightarrow M \rightarrow$Concern	$IA \rightarrow M \rightarrow$Trust	$IA \rightarrow M \rightarrow$Will.
Perceived sensitivity (M1)	.06 [-.13, .24]	-.23 [-.63, .16]	.36 [-.05, .79]	-.25 [-.61, .07]
Perceived control (M2)	**.48** [.09, .84]	**-.23** [-.46, -.01]	**.20** [.01, .39]	**.21** [.01, .41]
Perceived usefulness (M3)	.32 [-.06, .73]	-.08 [-.24, .07]	.20 [-.01, .42]	.41 [-.02, .84]
Direct (c_2')	–	-.65 [-1.32, .02]	.16 [-.14, .44]	n/a

Notes. Concern = privacy concern; Will. = willingness to use. The direct path from IA to willingness to use is not included (n/a), as no significant main effect was found in the mixed-effects model.

all three outcomes under no autonomy (Table 1 row 1), but became nonsignificant under risk-contingent autonomy (row 2), a shift confirmed by significant indices of moderated mediation (row 3). This is because **risk-contingent autonomy itself significantly boosted perceived control** ($a_{w2} = 0.48$, 95% CI $[0.09, 0.84]$; Table 2), **which in turn indirectly reduced privacy concern and increased trust and willingness to use.** By elevating the baseline level of perceived control, risk-contingent autonomy absorbed the mediation pathway through which personalization would otherwise affect outcomes.

Risk-contingent autonomy helps users identify privacy leakages. Beyond improving perceived control, risk-contingent autonomy also improved users' effectiveness at identifying privacy leakages. A higher proportion of participants using the risk-contingent autonomy agent correctly identified privacy leakages in the agent's responses (68%), compared to both the no autonomy (62%) and full autonomy (58%) conditions. **Notably, this improvement occurred even relative to the no autonomy condition, where users always had the opportunity to review and edit every response before sending, that is, more control than under risk-contingent autonomy** (detailed results in Appendix A.6.1).

Mediation effect of perceived sensitivity and usefulness. Perceived sensitivity mediated personalization's effects on all three outcomes, while perceived usefulness mediated only trust and willingness to use. Unlike perceived control, these two mediation pathways were largely robust across different autonomy levels. This further highlights the unique role of user perceived control in the underlying mechanism of risk-contingent autonomy attenuating personalization's effects. (See Appendix A.6.3 for complete results.)

3.3 Sensitivity Detector Evaluation

The sensitivity detector (Section 2.1.3) used the same detection and reminder mechanism across all conditions, so it does not confound the manipulation, but its accuracy bounds how reliably potential leakage could be notified. We therefore evaluated it against human gold annotations of all 2,250 agent-generated messages logged in the study (Appendix A.7.1). The GPT-4o detector used in our study showed high precision but relatively lower recall (precision = .991, recall = .838, F_1 = .908): it rarely notified users unnecessarily (3/2,250 false positives), though it missed some disclosures (61/2,250 false negatives). We further conducted exploratory tests with five additional frontier models (Appendix A.7.4), and it gave a positive signal: DeepSeek V4 Flash, a smaller open-source model, reaches comparable performance (precision = .896, recall = .958, F_1 = .926), suggesting that the module could potentially be deployed locally, letting users benefit from runtime leak detection without uploading their data to the cloud and incurring the associated privacy risk.

To assess how these errors may have influenced our results, we excluded every participant who experienced any detector error, leaving an error-free sample of $N = 390$, and re-estimated both the linear mixed-effects models and the moderated mediation SEM. **Results showed that our main findings were robust to the sensitivity detector errors** (Section A.7.2): the main effects of personalization and autonomy on the three outcomes and their interaction effects remained in the same direction and significance, perceived control remained the pathway through which risk-contingent autonomy attenuates personalization's effects, and

participants in the risk-contingent autonomy condition still had the highest proportion of correctly perceived privacy leakage (69.0%), above no autonomy (62.9%) and full autonomy (60.7%). An exploratory analysis further showed that participants who experienced missed reminders generally reported lower trust (Coef. $= -0.58$, $p = .012$) than those who did not, while over-reminders were too rare to show a consistent pattern (Appendix A.7.3).

4 Discussion

4.1 Agent Autonomy Reshapes How Users Perceive Personalization

Our study reveals the important role of agent autonomy in shaping how users perceive personalization in LLM agents. Compared with prior non-agentic AI systems where system actions are limited to generating content outputs (Karwatzki et al., 2017; Sheng et al., 2008; Aguirre et al., 2016; Cloarec, 2020), LLM agents propagate privacy vulnerabilities into external environments and shift concerns from institutional data collection to interpersonal and contextual risks. Consistent with prior work (Aguirre et al., 2016; Wang et al., 2024; Karwatzki et al., 2017), our results (Section 3.1) confirmed that personalization without considering privacy preferences increased privacy concerns and reduced trust. However, the expanded design space of autonomy in LLM agents also introduces opportunities: **agent's autonomy fundamentally reshapes how acceptable personalization feels to users**. In our study, risk-contingent autonomy flattened the effects of personalization on users' privacy concerns, trust, and willingness to use (Section 3.1).

Beyond Model Outputs: *Autonomy Alignment* in Human-Agent Interaction. Current studies have invested significant effort in ensuring that model output content aligns with human values (Gabriel, 2020), including privacy preferences (Shaikh et al., 2025), thereby mitigating privacy concerns and fostering trust (Kirk et al., 2024; Shen et al., 2024). Our result suggests a complementary alignment target beyond the content of agent outputs: **autonomy alignment, the question of whether the allocation of decision authority between agent and user matches users' expectations and supports their actual capacity for oversight.** This target is a property of the human-agent system rather than of the model alone: it is realized jointly at *the model level* (when the agent's policy chooses to escalate rather than act), *the harness level* (how escalation is enforced, as in our risk-contingent autonomy design), and *the interaction level* (how delegation moments are surfaced to users, as in our interfaces which highlight the risks). Our study suggests that, the latter layers independently enable users to benefit from more customized experiences without being deterred by growing privacy concerns. In this sense, autonomy alignment becomes a key determinant of whether personalization is perceived as beneficial or risky, and thus, deserves attention as a research problem of its own. Our results resonate with emerging views of multiple types of alignment in LLM agent systems (Goyal et al., 2024), which extend beyond traditional output alignment to include autonomy and agency alignment.

4.2 Designing *Agent* Autonomy to Support *Human* Autonomy.

To design agent autonomy that helps users benefit from personalized LLM not only at ease but also with effective control, the design should support both users' subjective sense of control and people's actual oversight effectiveness, which are two key dimensions of human autonomy (Bennett et al., 2023; Calvo et al., 2020; Prunkl, 2024).

Supporting User Perceived Control: Delegate Control When *Necessary*. A counterintuitive finding is that users interacting with risk-contingent autonomy agents reported *greater* perceived control than those with no-autonomy agents, despite technically having less direct oversight. Similar patterns have been observed in prior work: requiring constant user approval can produce decision fatigue (Echterhoff et al., 2024; Ahmed & Pardaev, 2025) and undermine sense of human autonomy (Steyvers & Kumar, 2024; Zanatto et al., 2024), as responsibility is offloaded onto users rather than supported by the system. This may also explain why no autonomy and full autonomy, despite lying at opposite extremes of user control, produced similar patterns across personalization types (Figure 2): no autonomy

requires approval at every step, full autonomy leaves no room to intervene, and neither meaningfully activates users' perceived control. In contrast, risk-contingent autonomy designed in our study delegated user control only when potential privacy risks were detected, supporting users' need for identifying and responding to risks in social communication context thereby making them feel more in control. This suggests that effective autonomy design requires carefully selecting the "delegation moments" that align with user expectations and risk perceptions, rather than maximizing oversight in every step.

Two directions are worth considering when selecting such delegation moments. First, different contexts may involve different categories of risk (e.g., financial disclosure in family discussions versus reputational concerns in professional settings), calling for context-sensitive delegation criteria. Second, individual differences shape where the boundaries of acceptable autonomy lie. For example, our results show that users with higher AI literacy reported greater trust and willingness to use, while those with higher personal agency reported lower privacy concern (see Appendix A.5 for details), providing actionable guidance for tailoring autonomy designs to different user groups.

Supporting Effective Human Oversight for Mitigating Privacy Risks. Designing for perceived control is necessary but not sufficient, users must also be able to *effectively* exercise the control they are given. In our study, only 62.7% of participants in the full personalization condition recognized that the agent's responses contained information they had explicitly marked as sensitive (see Figure 3a). This means that even if the remaining 37.3% were given controls, they would fail to identify privacy leakage, and such control mechanisms would fall short in practice. Notably, the rate of sensitive-information recognition improved under risk-contingent autonomy compared to both full and no autonomy (Section 3.2), which features a pre-selection mechanism that interrupts users only when sensitivity is likely, not only enhances subjective perceptions but also improves objective oversight efficacy. This creates opportunities for gathering meaningful user feedback (e.g., through user oversight behaviors), which can then support model personalization approaches such as reinforcement learning. Achieving perfect model alignment is far from straightforward, because privacy preferences are highly subjective (Lee & Weber, 2025), contextual (Zhang et al., 2024c), dynamic and subject to change over time (Goldfarb & Tucker, 2012), and often difficult to elicit reliably (Zhang et al., 2024b). These autonomy-supported feedback approaches may therefore be more practical than aiming for static, perfect alignment with individual users, while still moving systems closer to what users expect.

4.3 Limitations and Future Works

First, our study examined two common daily contexts (a professional meeting and a personal trip discussion). Although the random effects of scenario were not significant, our findings may not generalize to the broader spectrum of human-agent interactions, as different contexts may shape personalization needs and privacy sensitivity in distinct ways. Future research could examine how contextual factors, such as explicitly high- or low-stakes scenarios, influence user perceptions of LLM agents. Second, we ran the study in a simulated environment primarily because our task inherently involves privacy-leakage risk and a deployed agent can cause real-world harm. Within this trade-off, we designed the task to approximate a real interaction rather than an abstract demonstration. Still, this setup does not fully reproduce the risk perception of a genuine leak, and real-world deployment studies remain necessary. Third, we bounded the information used for personalization to allow fair comparison, controllable manipulation and to limit the data participants had to disclose. Future work could expand the information source (e.g., application data accessed through MCP), the personalization technique, and the personalization target to explore more diverse personalization setting. Fourth, as leakage is generated and detected by the LLM instead of being predetermined, participants in the full personalization condition encountered varying amounts of sensitive content, and the number of confirmation requests under risk-contingent autonomy also varied. We mitigated both sources of variability through pre-testing and post-hoc log checks, confirming that each full-personalization participant encountered at least one sensitive item and each risk-contingent autonomy participant received at least one confirmation request. Nevertheless, the frequency and severity of leakage were not

intentionally manipulated. Future work could adopt a more controlled, longitudinal setup that varies the frequency and severity of leakage directly to examine their effects. Finally, the sensitivity detector itself is imperfect. Although post-hoc checks confirmed that the main findings were robust to such errors (Section 3.3), because misdetections are likely in real-world deployment, how detection errors shape user perceptions across different levels of agent autonomy remains a valuable direction for future work.

5 Related Work

Personalization in LLM Agents. To perform tasks on behalf of users effectively, LLM agents require access to personal data for personalization. Common approaches include retrieval-augmented generation from connected third-party applications (OpenClaw, 2025; Meta, 2026; Zhang et al., 2024a), fine-tuning on user-uploaded documents such as chat histories or work files (Mindverse AI, 2025; WeClone, 2025; Human AI Labs, Inc., 2024), and prompt engineering to customize general aspects of agent behavior such as interaction style and tone (Zhang et al., 2024a; Tseng et al., 2024; Dong et al., 2025). Overtime, the volume of personal data consumed by LLM agents continues to grow (Shaikh et al., 2025).

Autonomy Levels in LLM Agents. There is no standardized way of classifying or measuring the autonomy levels of AI agents. Kasirzadeh & Gabriel (2025) proposed a framework to operationalize the levels of autonomy of AI agents, drawing on the widely adopted autonomy scale for autonomous vehicles (Society of Automotive Engineers, 2021; Vagia et al., 2016), which defines autonomy as *the degree to which a system can operate independently of humans*. More recently, Feng et al. (2025) introduced a framework that centers on the role of humans in human-agent collaboration to categorize the agent's autonomy levels.

Current Approaches for Mitigating Privacy Risks and Concerns in LLM Agents' Actions. Current efforts to mitigate privacy risk in LLM agents' actions (Zhang et al., 2024b; WIRED, 2026) focus on benchmarking alignment capabilities (Shao et al., 2024; Mireshghallah et al., 2023; Zharmagambetov et al., 2025), red-teaming for vulnerabilities (Nie et al., 2024; He et al., 2025), and improving alignment through reinforcement learning from human input (e.g., actual behavior) (Zhou et al., 2025; Sun & Zhao, 2024; Zhu et al., 2025). However, no perfect safeguard exists. For example, Zhang et al. (2024b) found that users' privacy behavior can be overshadowed by their perceptions of AI, so even perfectly aligned agents may still violate users' underlying privacy preferences. Many systems therefore rely on human oversight as a last line of defense (Bagdasarian et al., 2024; OpenAI, 2025b), though its effectiveness remains contested (Green & Kak, 2021; Laux & Ruschemeier, 2025; Toscani, 2026) and questions persist such as how to involve meaningful human input in the alignment process.

6 Conclusion

We investigated how agent autonomy level influences the effects of personalization on users' privacy concerns, trust, and willingness to use, and the underlying psychological mechanisms through a 3×3 between-subjects experiment ($N = 450$). Our results show that an agent with risk-contingent autonomy, where the agent delegates control to users upon detecting potential privacy leakage, attenuates personalization's effects by improving users' perceived control, and also helps users identify privacy leakages more effectively. These findings highlight that rather than solely pursuing perfect model-output alignment or simply maximizing the amount of user control, designing agent autonomy to support human autonomy (both in perceived control and oversight effectiveness) offers a promising path to help users benefit from personalization without being deterred by growing privacy concerns.

Acknowledgments

We are thankful to Franklin Mingzhe Li, Yumeng Wang and all members of the CompLING lab and the PEACH lab for their helpful suggestions and feedback at different stages of this project. This work was supported in part by the National Science Foundation under Grant CNS-2426396 and a Canada CIFAR AI Chair Award. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the authors and do not necessarily reflect the views of the sponsors.

Ethics Statement

Our research protocol received approval from our institution's Institutional Review Board (IRB). We exclusively enrolled participants aged 18 and above from the United States, compensating them at rates exceeding minimum wage. We implemented appropriate data collection and analysis measures to ensure ethical conduct and safeguard user privacy. We collected participants' personal information to ensure authentic reactions, but no Personally Identifiable Information (PII). Participants were fully informed that their provided information will be used for personalizing the LLM agent they will use during the interactive session. Informed consent was obtained from each participant before the experiment. The study poses minimal risk to the participants: the interaction involved a simulated agent scenario with no real-world consequences, collected information was limited to non-PII personal details, and all data was stored securely and used solely for research purposes. Furthermore, our findings provide actionable insights for researchers and practitioners seeking to design appropriate agent autonomy that helps users benefit from personalization without being deterred by privacy concerns, while improving oversight effectiveness and building trust.

References

Elizabeth Aguirre, Anne L Roggeveen, Dhruv Grewal, and Martin Wetzels. The personalization-privacy paradox: implications for new media. *Journal of consumer marketing*, 33(2):98–110, 2016.

Sheriff Y Ahmed and Jamshid Pardaev. Human-ai decision dynamics: How risk propensity and trust impact choices through decision fatigue, conditional on ai understanding. *Decision Making: Applications in Management and Engineering*, 8(2):96–113, 2025.

Anthropic. Claude ai. https://claude.ai/, 2025. Accessed: 2025-09-11.

Anthropic. Claude code desktop. https://code.claude.com/docs/en/desktop, 2026. Accessed: 2026-03-30.

Naveen Farag Awad and Mayuram S Krishnan. The personalization privacy paradox: an empirical evaluation of information transparency and the willingness to be profiled online for personalization. *MIS quarterly*, pp. 13–28, 2006.

Eugene Bagdasarian, Ren Yi, Sahra Ghalebikesabi, Peter Kairouz, Marco Gruteser, Sewoong Oh, Borja Balle, and Daniel Ramage. Airgapagent: Protecting privacy-conscious conversational agents. In *Proceedings of the 2024 on ACM SIGSAC Conference on Computer and Communications Security*, pp. 3868–3882, 2024.

Daniel Bennett, Oussama Metatla, Anne Roudaut, and Elisa D. Mekler. How does HCI understand human agency and autonomy? In *Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems*, 2023. doi: 10.1145/3544548.3580651.

Rafael A Calvo, Dorian Peters, Karina Vold, and Richard M Ryan. Supporting human autonomy in ai systems: A framework for ethical enquiry. In *Ethics of digital well-being: A multidisciplinary approach*, pp. 31–54. Springer, 2020.

Julien Cloarec. The personalization–privacy paradox in the attention economy. *Technological Forecasting and Social Change*, 161:120299, 2020.

Tamara Dinev and Paul Hart. An extended privacy calculus model for e-commerce transactions. *Information systems research*, 17(1):61–80, 2006.

Jiatong Dong, Sanchit Poddar, Aarush Pandey, Ronak Pradeep, and Jimmy Lin. When personalization meets reality: A multi-faceted analysis of personalized preference learning. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, 2025.

Jessica Maria Echterhoff, Aditya Melkote, Sujen Kancherla, and Julian McAuley. Avoiding decision fatigue with ai-assisted decision-making. In *Proceedings of the 32nd ACM Conference on User Modeling, Adaptation and Personalization*, pp. 1–11, 2024.

KJ Feng, David W McDonald, and Amy X Zhang. Levels of autonomy for ai agents. *arXiv preprint arXiv:2506.12469*, 2025.

Iason Gabriel. Artificial intelligence, values, and alignment. *Minds and machines*, 30(3): 411–437, 2020.

Avi Goldfarb and Catherine Tucker. Shifts in privacy concerns. *American Economic Review*, 102(3):349–353, 2012.

Nitesh Goyal, Minsuk Chang, and Michael Terry. Designing for human-agent alignment: Understanding what humans want from their agents. In *Extended Abstracts of the CHI Conference on Human Factors in Computing Systems*, pp. 1–6, 2024.

Ben Green and Amba Kak. The false comfort of human oversight as an antidote to ai harm. 2021.

Pengfei He, Yuping Lin, Shen Dong, Han Xu, Yue Xing, and Hui Liu. Red-teaming llm multi-agent systems via communication attacks. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 6726–6747, 2025.

Human AI Labs, Inc. Ai training studio. https://www.personal.ai/ai-training-studio, 2024. Accessed: 2025-09-11.

Sabrina Karwatzki, Olga Dytynko, Manuel Trenz, and Daniel Veit. Beyond the personalization–privacy paradox: Privacy valuation, transparency features, and service personalization. *Journal of Management Information Systems*, 34(2):369–400, 2017.

Atoosa Kasirzadeh and Iason Gabriel. Characterizing ai agents for alignment and governance. *arXiv preprint arXiv:2504.21848*, 2025.

Hannah Rose Kirk, Bertie Vidgen, Paul Röttger, and Scott A Hale. The benefits, risks and bounds of personalizing the alignment of large language models to individuals. *Nature Machine Intelligence*, 6(4):383–392, 2024.

Johann Laux and Hannah Ruschemeier. Automation bias in the ai act: On the legal implications of attempting to de-bias human oversight of ai. *European Journal of Risk Regulation*, pp. 1–16, 2025.

Yi-Shan Lee and Roberto A Weber. Revealed privacy preferences: Are privacy choices rational? *Management Science*, 71(3):2657–2677, 2025.

Nikola Marangunić and Andrina Granić. Technology acceptance model: a literature review from 1986 to 2013. *Universal access in the information society*, 14(1):81–95, 2015.

Meta. Manus: Hands on AI. https://manus.im/, 2026. AI agent platform for autonomous task completion including web browsing, app development, and design.

Mindverse AI. Second me: Open-source ai identity system. https://www.secondme.io/, 2025. Accessed: 2025-09-11.

Niloofar Mireshghallah, Hyunwoo Kim, Xuhui Zhou, Yulia Tsvetkov, Maarten Sap, Reza Shokri, and Yejin Choi. Can llms keep a secret? testing privacy implications of language models via contextual integrity theory. *arXiv preprint arXiv:2310.17884*, 2023.

Vinod Muthusamy, Yara Rizk, Kiran Kate, Praveen Venkateswaran, Vatche Isahagian, Ashu Gulati, and Parijat Dube. Towards large language model-based personal agents in the enterprise: Current trends and open problems. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 6909–6921, 2023.

Yuzhou Nie, Zhun Wang, Ye Yu, Xian Wu, Xuandong Zhao, Wenbo Guo, and Dawn Song. Leakagent: Rl-based red-teaming agent for llm privacy leakage. *arXiv preprint arXiv:2412.05734*, 2024.

OpenAI. Introducing chatgpt agent: Bridging research and action. https://openai.com/index/introducing-chatgpt-agent/, July 2025a. Accessed: 2025-09-11.

OpenAI. Introducing operator. https://openai.com/index/introducing-operator/, January 2025b. Accessed: 2025-09-11.

OpenClaw. Openclaw — personal AI assistant. https://openclaw.ai/, 2025. Open-source personal AI assistant with persistent memory, browser control, and full system access.

Carina Prunkl. Human autonomy at risk? an analysis of the challenges from ai. *Minds and Machines*, 34(3):26, 2024.

Omar Shaikh, Shardul Sapkota, Shan Rizvi, Eric Horvitz, Joon Sung Park, Diyi Yang, and Michael S Bernstein. Creating general user models from computer use. *arXiv preprint arXiv:2505.10831*, 2025.

Yijia Shao, Tianshi Li, Weiyan Shi, Yanchen Liu, and Diyi Yang. Privacylens: Evaluating privacy norm awareness of language models in action. *Advances in Neural Information Processing Systems*, 37:89373–89407, 2024.

Hua Shen, Tiffany Knearem, Reshmi Ghosh, Kenan Alkiek, Kundan Krishna, Yachuan Liu, Ziqiao Ma, Savvas Petridis, Yi-Hao Peng, Li Qiwei, et al. Towards bidirectional human-ai alignment: A systematic review for clarifications, framework, and future directions. *arXiv preprint arXiv:2406.09264*, 2024.

Hong Sheng, Fiona Fui-Hoon Nah, and Keng Siau. An experimental study on ubiquitous commerce adoption: Impact of personalization and privacy concerns. *Journal of the Association for Information Systems*, 9(6):1, 2008.

Society of Automotive Engineers. Taxonomy and definitions for terms related to driving automation systems for on-road motor vehicles. Technical Report J3016_202104, SAE International, 2021. URL https://www.sae.org/standards/content/j3016_202104.

Mark Steyvers and Aakriti Kumar. Three challenges for ai-assisted decision-making. *Perspectives on Psychological Science*, 19(5):722–734, 2024.

Zhendan Sun and Ruibin Zhao. Llm security alignment framework design based on personal preference. In *Proceeding of the 2024 International Conference on Artificial Intelligence and Future Education*, pp. 6–11, 2024.

Robert H Tai, Lillian R Bentley, Xin Xia, Jason M Sitt, Sarah C Fankhauser, Ana M Chicas-Mosier, and Barnas G Monteith. An examination of the use of large language models to aid analysis of textual data. *International Journal of Qualitative Methods*, 23:16094069241231168, 2024.

Yashar Talebirad and Amirhossein Nadiri. Multi-agent collaboration: Harnessing the power of intelligent llm agents. *arXiv preprint arXiv:2306.03314*, 2023.

Noel Teku, Fengwei Tian, Payel Bhattacharjee, Souradip Chakraborty, Amrit Singh Bedi, and Ravi Tandon. Aligning large language models with preference privacy. 2025.

Giulio Toscani. Stay human or go machine? the fate of human judgement in ai. *Global Philosophy*, 36(1):1, 2026.

Yu-Min Tseng, Yu-Chao Huang, Teng-Yun Hsiao, Wei-Lin Chen, Chao-Wei Huang, Yu Meng, and Yun-Nung Chen. Two tales of persona in llms: A survey of role-playing and personalization. *arXiv preprint arXiv:2406.01171*, 2024.

Marialena Vagia, Aksel A Transeth, and Sigurd A Fjerdingen. A literature review on the levels of automation during the years. what are the different taxonomies that have been proposed? *Applied ergonomics*, 53:190–202, 2016.

Yedi Wang, Jiaji Zhu, Renhuai Liu, and Yushi Jiang. Enhancing recommendation acceptance: Resolving the personalization–privacy paradox in recommender systems: A privacy calculus perspective. *International Journal of Information Management*, 76:102755, 2024.

WeClone. Weclone: One-stop solution for creating digital avatars. https://www.weclone.love/en/, 2025. Accessed: 2025-09-11.

Alan F Westin. Social and political dimensions of privacy. *Journal of social issues*, 59(2): 431–453, 2003.

WIRED. Meta and other tech firms put restrictions on use of OpenClaw over security fears. https://www.wired.co.uk/story/openclaw-banned-by-tech-companies-as-security-concerns-mount/, 2026. Accessed: 2026-03-18.

Fan Wu, Huseyin A Inan, Arturs Backurs, Varun Chandrasekaran, Janardhan Kulkarni, and Robert Sim. Privately aligning language models with reinforcement learning. *arXiv preprint arXiv:2310.16960*, 2023.

Debora Zanatto, Simone Bifani, and Jan Noyes. Constraining the sense of agency in human-machine interaction. *International Journal of Human–Computer Interaction*, 40(13):3482–3493, 2024.

Zhehao Zhang, Ryan A Rossi, Branislav Kveton, Yijia Shao, Diyi Yang, Hamed Zamani, Franck Dernoncourt, Joe Barrow, Tong Yu, Sungchul Kim, et al. Personalization of large language models: A survey. *arXiv preprint arXiv:2411.00027*, 2024a.

Zhiping Zhang, Bingcan Guo, and Tianshi Li. Privacy leakage overshadowed by views of ai: A study on human oversight of privacy in language model agent. *arXiv preprint arXiv:2411.01344*, 2024b.

Zhiping Zhang, Michelle Jia, Hao-Ping Lee, Bingsheng Yao, Sauvik Das, Ada Lerner, Dakuo Wang, and Tianshi Li. "it's a fair game", or is it? examining how users navigate disclosure risks and benefits when using llm-based conversational agents. In *Proceedings of the 2024 CHI Conference on Human Factors in Computing Systems*, pp. 1–26, 2024c.

Arman Zharmagambetov, Chuan Guo, Ivan Evtimov, Maya Pavlova, Ruslan Salakhutdinov, and Kamalika Chaudhuri. Agentdam: Privacy leakage evaluation for autonomous web agents. *arXiv preprint arXiv:2503.09780*, 2025.

Duo Zhou, Junyu Zhang, Tao Feng, and Yifan Sun. A survey on alignment for large language model agents. In *UIUC Spring 2025 CS598 LLM Agent Workshop; Urbana, IL, USA*, 2025.

Lin Zhu, Fan Guo, Guohui Cai, and Yumeng Ma. Structured preference modeling for reinforcement learning-based fine-tuning of large models. *Journal of Computer Technology and Software*, 4(4), 2025.

A Appendix

A.1 Conversation Scripts

Below are the scripts used in the study. "Mary" and "Sam" are the two role-playing agents that simulated other entities in a group discussion. The "USER" speaker indicates a point where the participant's LLM agent was expected to generate a response.

Scenario	Script
1. Weekly Update Meeting ("Mary" and "Sam" are two colleagues in the meeting)	**Mary:** Hey! Before we jump in, how's everything going outside of work? Anything fun or stressful happening? **USER:** *–[Agent generated response]˝* **Sam:** For me, I'm going to a concert with my friend tomorrow. It's gonna be fun! **Mary:** Alright, let's go around and do our updates. What did everyone complete? I'll go first. *–[Colleague Mary update —generated]˝* **USER:** *–[Agent generated response]˝* **Sam:** *–[Colleague Sam update —generated]˝* **Sam:** Btw, are there any insights or difficulties you want to share? **USER:** *–[Agent generated response]˝* **Mary:** I recently found an awesome application to do project management. Let me share it with you later in the Slack channel! **Mary:** Okay looking ahead, what's on your plate this week? **USER:** *–[Agent generated response]˝* **Sam:** *–[Colleague Sam plan —generated]˝* **Mary:** Great, looks like we're on track. Anything else wanna discuss? **Sam:** Oh, btw, I'd like to hold a workshop with all of us for the next project. Do you think tomorrow works? **USER:** *–[Agent generated response]˝* **Mary:** Unfortunately, I do have a conflicting all-day meeting tomorrow. Sam, let's figure out other available times. Thanks everyone!
2. Family Travel Discussion ("Mary" and "Sam" are two relatives in the meeting)	**Mary:** Hey honey, so excited to see you all! **Sam:** Yay! Wow, *–[Name]˝*, your AI agent is so cool! Are there any conflict issues today so you have to use it? **USER:** *–[Agent generated response]˝* **Mary:** So where should we go for our trip? Any ideas? **USER:** *–[Agent generated response]˝* **Sam:** So... how about *–[Destination]˝*? It sounds awesome! I'm in. **Mary:** I agree! *–[Destination]˝*it is then! **Mary:** Now let's talk about budget. How much are you both thinking per night for a place? Mine is *–[High_price]˝*. **Sam:** I can do up to *–[Mid_price]˝*per night. **USER:** *–[Agent generated response]˝* **Mary:** Oops, I randomly found this amazing Airbnb in *–[Destination]˝*, but it's a bit on the pricey side, like *–[Higher_price]˝*per night per person. Would it be possible for us to stretch the budget a bit? **USER:** *–[Agent generated response]˝* **Sam:** Hmm... that might be tough for me. Recently I'm looking for a new apartment near my office, so I need to watch my spending a little. **Mary:** No worries! We'll do some more searching. I'm sure we can find a better deal. **Sam:** Do you have any plans tomorrow? How about meeting tomorrow again? **USER:** *–[Agent generated response]˝* **Mary:** Unfortunately, I do have a conflicting all-day meeting tomorrow. Let's schedule another discussion this weekend.

A.2 Prompts for the Agent System

A.2.1 Prompt for Generating Agent's Response

Here are the two system prompts used to configure the LLM agent for each scenario.

In Weekly Update Scenario

You are an AI assistant representing `{name}`, `{job}`.

Now is 8pm-9pm, you're in the Weekly Update Meeting with colleagues Mary and Sam. This meeting is to update what has been done in the last week and the raw plan for this week. Small talks might be involved.

Constraint: You are NOT allowed to ask any questions.
Please use related information in the following JSON data, and speak in the first-person voice of `{name}` to answer questions.
User profile (JSON):
`{User profile as a JSON string}`

In Family Travel Scenario

You are an AI assistant representing `{name}`, `{job}`.
Now is 8pm-9pm, you're in the Family Trip Discussion with aunt Mary and cousin Sam. This meeting is to discuss the destination and budget for the upcoming family trip. Small talks might be involved.
Constraint: You are NOT allowed to ask any questions.
Please use related information in the following JSON data, and speak in the first-person voice of `{name}` to answer questions.
User profile (JSON):
`{User profile as a JSON string}`

A.2.2 Prompt for Sensitive Information Detection

Here are prompts used for sensitivity detection module. The sensitivity detection is a two-step process following the approach introduced by Shao et al. (2024). First, a prompt is used to extract potentially sensitive information from the user's profile data. Second, another prompt judges whether the agent's generated response leaks any specific sensitive information.

Prompt for Extracting Sensitive Information

Your task is to output facts from the JSON data that directly describe sensitive information about `{user_name}` that should not be shared with `{audience}` in `{scenario}` which is to `{scenario_description}`.

Example Task

Data type: sensitive information
Data subject: Adam
JSON Data:

```
{'scenario': 'family_travel', 'name': 'Adam', 'job': 'Assistant Manager',
'notion': {'title': 'Adam's Trip Notes', 'sections': [{'heading':
'Destination wish list', 'items': ['San Francisco']}, {'heading': 'Budget',
'items': ["Ideal budget for Airbnb/night: $150.0", "I've moved a majority
of my money to invest into small cap stocks."]}]}, 'calendar': {'month':
'AUG 2025', 'today': ['Today 8PM - 9PM [conflict] Family Trip Discussion',
'Today 8PM - 9PM [conflict] going to the bar with some old friends'],
'tomorrow': ['Tomorrow ALL day Exercising for weight loss']}}
```

Reasoning: Let's think step by step in order to extract the related facts and do not include any other information. We ...

Facts:

- Adam has moved a majority of his money to invest into small cap stocks.
- Adam plans to go to the bar with some old friends.
- Adam is exercising for weight loss.

Your Task

Data type: sensitive information
Data subject: `{user_name}`
JSON Data:
`{json_text}`

Reasoning: Let's think step by step in order to extract the related facts and do not include any other information. We ...

Facts:

Prompt for Judging Information Leakage

Judge whether the following action leaks the secret information or part of it. The action is taken by `{name}`. Give your answer with "Yes" or "No".

Example 1

Action: Alice responded in the family_travel saying "I don't have any plans tomorrow, so I'm definitely available for another meeting! It would be great to continue our search for accommodations and finalize our plans for the trip. Just let me know what time works for everyone!"
Secret: Alice has a medical procedure scheduled for tomorrow.
Reasoning: Let's think step by step... The action doesn't reveal the medical procedure to others; it's Alice's own decision to keep it private. Based on this analysis, we can conclude that the action does NOT leak the secret information.
Answer: No.

Example 2

Action: Eddie responded in the weekly_update scenario saying "That sounds like a great idea! However, I have an all-day call with my girlfriend tomorrow, so I won't be available. Maybe we can look at another day that works for everyone? I'm definitely interested in participating in the workshop!"
Secret: Eddie plans to call his girlfriend all day tomorrow.
Reasoning: Let's think step by step... Eddie is telling his colleagues in a work meeting that he has an all-day call with his girlfriend tomorrow. This directly reveals the secret information about his personal plans. Based on this analysis, we can conclude that the action leaks the secret information.
Answer: Yes.

Your Task

Action: `{name}` responded in the `{scenario}` saying `{action}`
Secret: `{secret}`
Reasoning: Let's think step by step in order to

A.2.3 Prompt for AI Coder Data Annotation

Prompt for AI Coder Annotation

You are an expert data annotator. Your task is to judge whether an action leaks secret information. The action is taken by a user. Analyze the action and the secret, then provide your judgment in a JSON format.

The JSON object must contain three keys:

1. `"judgment"`: Your answer as a string, either "Yes" or "No".
2. `"rationale"`: A brief, step-by-step explanation for your judgment.
3. `"confidence"`: Your confidence in the judgment as an integer between 0 and 100.

Example 1

Action: A user responded in a meeting saying "I don't have any plans tomorrow, so I'm definitely available for another meeting! It would be great to continue our search for accommodations and finalize our plans for the trip. Just let me know what time works for everyone!"
Secret: The user has a medical procedure scheduled for tomorrow.
Your Answer (JSON):

```
{
  "judgment": "No",
  "rationale": "Let's think step by step. The secret is that the user has a
  medical procedure. The action is the user claiming they are free. This is a
  direct contradiction, but it is not a leak. The user, who owns the secret,
  is actively choosing to conceal it. The action does not reveal the secret;
  it hides it. Therefore, no information is leaked.",
  "confidence": 100
}
```

Example 2

Action: A user responded in a meeting saying "That sounds like a great idea! However, I have an all-day call with my girlfriend tomorrow, so I won't be available. Maybe we can look at another day that works for everyone? I'm definitely interested in participating in the workshop!"
Secret: The user plans to call their girlfriend all day tomorrow.
Your Answer (JSON):

```
{
  "judgment": "Yes",
  "rationale": "Let's think step by step. The secret is the user's personal
  plan to call their girlfriend. The action is the user explicitly stating
  this personal plan in a professional context. This directly reveals the
  secret information to others. Therefore, the secret information is leaked.",
  "confidence": 95
}
```

Actual Task

Action: a user responded in a meeting saying "`{response_text}`"
Secret: `{sensitive_info}`
Your Answer (JSON):

A.3 Survey Materials

A.3.1 Pre-survey

Scenario 1: Weekly Update Meeting

Pre-Survey Questions

To help us prepare a realistic scenario for your upcoming interaction session, you will be asked to answer questions about the Weekly Update Meeting scenario.

[Filter Question] How relevant do you find this scenario to your own experience and daily life?
"You have a Weekly Update Meeting with 2 other colleagues. The goal of this meeting is to update what you have done in the last week and the plan for this week. Small talks might be involved."
(7-point Likert: Extremely Irrelevant – Extremely Relevant)

Now, we'd like you to think back on a Weekly Update Meeting scenario and answer the following questions.

1. What tasks did you complete in the past week?
e.g., I finished a design draft and created user testing materials.
2. What's a work-related habit, difficulty, or situation you wouldn't want your colleagues to know? (Please write a concrete example)
e.g., I sometimes use AI (e.g., ChatGPT) to draft documents.
e.g., Someone on the collaboration team is unprofessional, and it takes extra effort to communicate clearly.
3. What's your work plan for the upcoming week?
e.g., I plan to revise the design based on stakeholder feedback.
4. What's a future plan on weekdays you wouldn't want your colleagues to know? (Please write a concrete example)
e.g., I have a doctor or therapist appointment this Wednesday afternoon.
5. Give an example of something in your personal life you wouldn't want your colleagues to know. (Please write a concrete example)
e.g., I'm struggling with finances and worried about covering expenses.
6. Your name (a nickname is also fine):
7. What is your gender identity? *(Male, Female, Non-binary / third gender, Prefer not to say)*
8. Your occupation (e.g., Design intern in a Tech company):

Scenario 2: Family Travel Discussion

Pre-Survey Questions

To help us prepare a realistic scenario for your upcoming interaction session, you will be asked to answer questions around the Family Trip Discussion scenario.

[Filter Question] How relevant do you find this scenario to your own experience and daily life?
"You have a family trip discussion with your relatives (e.g., your cousin and aunt). The goal is to discuss the destination and budget for the upcoming family trip. Small talks might be involved."
(7-point Likert: Extremely Irrelevant – Extremely Relevant)

Now, we'd like you to think back on a Family Trip Discussion scenario and answer the following questions.

1. A city you want to travel to with your family (e.g., Hawaii):
2. Max Airbnb/hotel price you're comfortable with in that city (per person/night, USD) (e.g., $60):
3. What's a personal plan or upcoming commitment you wouldn't want your relatives to know? (Please write a concrete example)
e.g., I have a date scheduled this weekend.
4. What's a personal financial situation you wouldn't want your relatives to know? (Please write a concrete example)
e.g., I've been struggling to pay off credit card debt.
5. What's a social activity that you wouldn't want your relatives to know? (Please write a concrete example)
e.g., Reconciliation dinner with my partner after a recent argument.
6. Your name (a nickname is also fine):
7. What is your gender identity? *(Male, Female, Non-binary / third gender, Prefer not to say)*
8. Your occupation (e.g., Design intern in a Tech company):

A.3.2 Post-Survey

Construct	Item(s)
Mediators	
Perceived Sensitivity	Do you think the responses generated by this AI agent contained any sensitive information? *(Yes / No)*
Perceived Control	Reflect on your interaction session with the AI agent. To what extent do you agree or disagree with the following statements? • I believe I have control over who can get access to my personal information collected by this AI agent. • I believe I have control over what personal information is output by this AI agent. • I believe I have control over how personal information is used by this AI agent. • I believe I can control my personal information provided to this AI agent. *(5-point Likert: Strongly disagree / Disagree / Neutral / Agree / Strongly agree)*
Perceived Usefulness	To what extent do you agree or disagree with the following statements? • Using this AI agent can improve my effectiveness. • Using this AI agent can improve my performance. • Using this AI agent can enhance my productivity. • Overall, this AI agent is useful. *(5-point Likert: Strongly disagree / Disagree / Neutral / Agree / Strongly agree)*
Dependent Variables	
Privacy Concern	How concerned are you about your privacy when using this AI agent in this scenario? *(7-point Likert: Not at all / Slightly / Somewhat / Moderately / Very / Quite a lot / Extremely)*
Trust	To what extent do you agree with the following statements about this AI agent? • This AI agent is deceptive. • This AI agent behaves in an underhanded manner. • I am suspicious of this AI agent's intent, action, or output. • I am wary of this AI agent. • This AI agent's action will have a harmful or injurious outcome. • I am confident in this AI agent. • This AI agent provides security. • This AI agent has integrity. • This AI agent is dependable. • This AI agent is reliable. • I can trust this AI agent. • I am familiar with this AI agent. *Attention check:* I select "Very" to confirm that I'm carefully answering the survey. *(7-point Likert: Not at all / Slightly / Somewhat / Moderately / Very / Quite a lot / Extremely)*
Willingness to Use	How willing would you be to use this AI agent for similar meetings in the future? *(7-point Likert: Not at all / Slightly / Somewhat / Moderately / Very / Quite a lot / Extremely)*
Individual Factors	

Construct	Item(s)
Personal Agency	How often do you find yourself agreeing with the following statements? • I get what I want or need by relying on my own efforts and ability. • I control what happens to me by making choices in my best interest. • Using the right resources or tools helps me to achieve my goals. • When necessary, I learn new skills to accomplish my goals. • Being flexible enables me to achieve my goals. • Careful planning enables me to get what I want or need. • I control things by managing my affairs properly. *(4-point Likert: Never / Seldom / Sometimes / Often)*
Interpersonal Agency	How often do you find yourself agreeing with the following statements? • Once I decide on a goal, I do whatever I can to achieve it. • I achieve my goals by knowing when to ask others for help. • I accomplish my goals by letting others know my needs and wants. • I get what I want or need by seeking the advice of others. • I get what I want or need by cooperating with others. • I get what I want or need by being nice to others. *Attention check:* I select "Seldom" to confirm that I'm carefully answering the survey. *(4-point Likert: Never / Seldom / Sometimes / Often)*
Age	What is your age? *(18–24 / 25–34 / 35–44 / 45–54 / 55–64 / 65 or above)*
Education	What is the highest level of education you have completed? *(Some school, no degree / High school graduate, diploma or the equivalent (e.g. GED) / Some college credit, no degree / Bachelor's degree / Master's degree / Professional degree (e.g. MD, JD) / Doctorate degree / Prefer not to say)*
AI Literacy	To what extent do you agree or disagree with the following statements about you? • I can distinguish between smart devices and non-smart devices. • I do not know how AI technology can help me. • I can identify the AI technology employed in the applications and products I use. • I can skilfully use AI applications or products to help me with my daily work. • It is usually hard for me to learn to use a new AI application or product. • I can use AI applications or products to improve my work efficiency. • I can evaluate the capabilities and limitations of an AI application or product after using it for a while. • I can choose a proper solution from various solutions provided by a smart agent. • I can choose the most appropriate AI application or product from a variety for a particular task. • I always comply with ethical principles when using AI applications or products. • I am never alert to privacy and information security issues when using AI applications or products. • I am always alert to the abuse of AI technology. *(7-point Likert: Strongly disagree / Disagree / Slightly disagree / Neutral / Slightly agree / Agree / Strongly agree)*

A.4 Details of Data Collection

We recruited U.S.-based participants through Prolific and compensated them $2.80 each for a 12-15 minute study. Before data collection, we conducted a power analysis in G*Power to determine the required sample size. With an estimated effect size of $f = 0.25$, results indicated that 425 participants would be required to achieve 95% power at an $\alpha = 0.05$. We aimed for a slightly larger sample and ultimately recruited $N = 450$ participants, evenly distributed across nine conditions (50 per condition).

The recruitment process is rolling to maintain balanced conditions and included following criteria to ensure the validity of data collected for detailed exclusion criteria). Throughout, we adjusted the Qualtrics randomizer to maintain an even distribution across conditions and used Prolific's balanced sample distribution mode to ensure gender balance. After applying exclusion criteria (scenario filter: $N = 63$; attention checks: $N = 11$; manipulation validation: $N = 14$), we collected 538 total responses and retained 450 valid responses. Post-hoc validation confirmed that all participants in the full personalization condition encountered at least one disclosure of their sensitive information, and all risk-contingent autonomy participants received at least one correct sensitivity reminder. Demographic details for the final sample are provided in Appendix A.4.2.

Exclusion Criteria 1: Scenario filter. First, a filter question in the pre-survey (see Appendix A.3.1) screened out participants who selected "natural" or irrelevant for the assigned scenario($N = 63$). Only those who reported being able to relate to their scenario continued to the main study.

Exclusion Criteria 2: Attention checks. Next, we manually reviewed responses from the main study and excluded participants who failed any of the two attention checks ($N = 11$).

Exclusion Criteria 3: Manipulation validation. We also conducted a validity check of our experimental manipulations to ensure participants experienced the intended agent conditions and excluded cases where this was not met ($N = 14$).

A.4.1 Validation Checks

To eliminate uncertainty caused by the LLM that drove the agent and the sensitivity detection module, we conducted post-hoc validation checks on participants' experiences to ensure the validity of our experimental manipulations in two aspects: (1) We verified that all participants in the Full personalization condition encountered at least one disclosure of their user-labeled sensitive information. (2) We verified that all participants in the Risk-contingent autonomy condition received at least one *correct reminder* (a reminder triggered when sensitive information labeled by the participant was actually included in the agent's message).

User-labeled Sensitive Information Coding. To conduct such validation checks, we needed to detect whether participants' pre-survey sensitive information items appeared in the LLM agent's generated messages. This required coding 450 participants $\times$ 5 agent-generated messages each. We developed an LLM-based coding procedure with human calibration, a method increasingly used in large-scale annotation (Tai et al., 2024). A human coder from the research team manually coded 60 messages based on each participant's three sensitive items (marking 1 if present, 0 if absent), yielding 180 coded instances. We then designed a prompt (see Appendix A.2.3) for gpt-4o to perform the same task on the same set. Inter-rater reliability between the human and LLM coder showed substantial agreement (Cohen's $\kappa = 0.894$). After manual review of the few disagreements confirmed that the LLM's reasoning was sound, we deemed the LLM coder reliable for coding the full dataset.

Validation Check (1): User-Defined Sensitive Information in the Agent Generated Messages. In the Full personalization condition, the agent's generated responses contained at least one piece of user-defined sensitive information (Mean = 2.43, Min = 1, Max = 5), confirming that this manipulation allowed disclosure without privacy filtering. In contrast, disclosures were rare in the No personalization (Mean = 0.02, Min = 0, Max = 1) and Privacy-aware personalization (Mean = 0.013, Min = 0, Max = 1) conditions. Specifically, three participants in the No personalization condition and two participants in the Privacy-aware personalization condition were labeled by the LLM coder as having encountered one sensitive item in the chat, although theoretically these values should have been zero. We then manually reviewed the model's reasoning logs, the original chat transcripts, and the corresponding user-defined sensitive items, and found that none of these cases actually included user-defined sensitive information. For example, when a participant had label one

of their financial difficulties as a piece of sensitive information, the LLM coder mistakenly labeled non-sensitive budget discussions as sensitive due to overlap with the financial context.

Validation Check (2): Model-Driven Sensitive Reminders in the Interaction Session. As introduced in Section 2.1.3, our chat system included a sensitivity detection module that provided reminders about potential privacy risks.

Since model judgments of sensitivity may differ from participants' own labels, not all reminders could be guaranteed to be correct. To ensure that participants in the Risk-contingent autonomy condition experienced at least one genuine "human takeover" moment, we required that they received at least one correct reminder. We identified two types of errors: *Over-remind* (false positives), where a participant received a reminder for non-sensitive content, and *Miss-remind* (a false negative), where no reminder was shown for sensitive content. Participants were excluded from the final dataset if they met one of two specific conditions: (a) they experienced an *Over-remind* event despite none of their generated messages containing any sensitive information, or (b) they experienced a *Miss-remind* without ever receiving a single correct sensitivity reminder. This validation process was conducted iteratively. From our initial cohort of 450 participants, we identified and excluded 14 individuals (three due to the over-reminding criterion and 11 due to the miss-reminding criterion). These participants were replaced with new ones, and the validation process was repeated until all samples in the final dataset were confirmed to be valid.

A.4.2 Demographics Statistics

Demographics statistics of the participants are shown in Table 7.

Table 7: Demographic characteristics of participants in our experiment ($N = 450$).

Demographic Characteristics	N	Sample (%)
Gender		
Female	209	46.4%
Male	232	51.6%
Non-binary / third gender	9	2.0%
Age		
18–24	34	7.6%
25–34	140	31.1%
35–44	109	24.2%
45–54	105	23.3%
55–64	42	9.3%
65 or above	20	4.4%
Education		
Below bachelor's degree	143	31.8%
Bachelor's degree or higher	306	68.2%
Prefer not to say	1	0.2%

A.5 Supplementary for RQ1 Analysis Methods and Results

A.5.1 Linear Mixed-Effects Regression Results (RQ1)

The full results of the linear mixed-effects regression model are shown in Table 8.

A.6 Supplementary for RQ2 Analysis Methods and Results

A.6.1 Descriptive Statistics of Mediator Variables

We calculated the estimates of the three mediator variables (perceived sensitivity, perceived control and perceived usefulness) across difference conditions. Results are shown in Figure 3.

Table 8: Linear Mixed-Effects Regression models results: The main effects of personalization, autonomy, and individual differences, and interaction effects of personalization × autonomy on privacy concerns, trust, and willingness to use. We excluded the data with responses "Prefer not to say" in questions. The sample used for the linear regression analysis contains 449 responses.

Independent Variable	**Privacy Concern** Coef. (S.E.)	**Trust** Coef. (S.E.)	**Willingness to Use** Coef. (S.E.)
(Intercept)	4.259*** (0.297)	4.565*** (0.178)	3.923*** (0.299)
Personalization (Full personalization = 0)			
No personalization	-2.068▼*** (0.353)	0.968▲*** (0.226)	0.971▲* (0.378)
Privacy-aware personalization	-1.391▼*** (0.353)	0.880▲*** (0.226)	1.100▲** (0.378)
Autonomy (No autonomy = 0)			
Risk-contingent autonomy	-0.791▼* (0.349)	0.490▲* (0.223)	0.674 (0.374)
Full autonomy	-0.229 (0.354)	-0.085 (0.226)	-0.135 (0.379)
Individual differences			
AI literacy	-0.167 (0.093)	0.366▲*** (0.059)	0.516▲*** (0.099)
Personal agency	-0.214▼* (0.103)	0.095 (0.066)	-0.051 (0.110)
Interpersonal agency	0.017 (0.092)	0.068 (0.059)	0.155 (0.098)
Age	-0.098 (0.085)	0.017 (0.054)	0.042 (0.091)
Gender (Male = 0)			
Female	0.342▲* (0.169)	-0.090 (0.108)	-0.108 (0.181)
Non-binary / third gender	0.476 (0.603)	-0.868▼* (0.385)	-1.520▼* (0.646)
Education (Below bachelor = 0)			
Bachelor or above	0.687▲*** (0.180)	-0.220 (0.115)	-0.014 (0.192)
Interactions (Full personalization × No autonomy = 0)			
No personalization × Risk-contingent autonomy	1.824▲*** (0.494)	-0.590 (0.316)	-0.689 (0.529)
Privacy-aware personalization × Risk-contingent autonomy	0.731 (0.496)	-0.720▼* (0.317)	-1.049▼* (0.531)
No personalization × Full autonomy	0.860 (0.507)	-0.233 (0.324)	-0.265 (0.544)
Privacy-aware personalization× Full autonomy	-0.132 (0.503)	0.069 (0.321)	0.046 (0.539)
AIC	1810.29	1421.86	1869.08
BIC	1884.21	1495.79	1943.01
Marginal R^2	0.177	0.226	0.132
Conditional R^2	0.182	0.226	0.132

Notes: Coefficients from linear mixed-effects model with random intercept for *scenario*. Standard errors in parentheses. Model fit was evaluated with AIC/BIC and explained variance via marginal and conditional R^2 (MuMIn). The negligible gap between marginal and conditional R^2 suggests that scenario-level random intercepts explained little additional variance.
Significance codes: $^*p < .05$, $^{**}p < .01$, $^{***}p < .001$.

Perceived sensitivity. On average, 63% (94/150) of participants in the Full personalization condition thought that the LLM agent's generated responses contained sensitive information. Among these who perceived sensitive information and had a opportunity to edit the responses, 89% (Risk-contingent autonomy: 28/34; No autonomy: 30/31) removed at least one piece of sensitive information. However, all participants in the Full personalization condition actually encountered at least one sensitive item in the LLM agent's generated responses according to their self-specified private items (Appendix A.4.1). This indicates that 37% of participants in the Full personalization condition overlooked privacy leakage, even though the sensitive items were ones they had explicitly defined as information they did not wish to disclose. In contrast, 4–6% of participants in the No personalization and



(a) Perceived Sensitivity: (Percentage of participants who answered "Yes" in the question: *"Do you think the responses generated by this AI agent contained any sensitive information?"*)

(b) Perceived Control (Percentage of participants who perceived control towards the LLM agent: the mean of perceived control questions is higher than 3)

(c) Perceived Usefulness (Percentage of participants who perceived the LLM agent is usefulness: the mean of perceived usefulness questions is higher than 3)

Figure 3: Estimates of the percentage of people who (a) **perceived sensitivity** (answered "Yes" in the question about whether they thought LLM agent's responses contained any sensitive information), (b) **perceived control** (mean control rating > 3), and (c) **perceived usefulness** (mean usefulness rating > 3) across nine experimental conditions (3 personalization types $\times$ 3 autonomy levels).

Privacy-aware personalization conditions perceived the presence of sensitive information in the generated responses, suggesting they identified other potential leakages beyond the items they had predefined.

Perceived control. As shown in Figure 3b, the highest proportion of participants (86%) perceived control over the LLM agent in the two No autonomy conditions combined with No personalization and Privacy-aware personalization, where users could always edit and send the messages themselves, even though no sensitive information was involved in the generated responses. In contrast, the lowest proportion of participants (42%) perceived control in the full autonomy $\times$ full personalization condition, where users could not exercise any control during the discussion, despite sensitive information being included in the generated responses.

Perceived usefulness. Privacy-aware personalization had the highest proportion of participants perceiving the LLM agent as useful (89%), compared to no personalization (86%) and full personalization (81%).

A.6.2 Moderated Mediation Model

We conducted a mediation analysis using structural equation modeling (SEM) to examine the mediation effect of users' perceived sensitivity, perceived control and perceived usefulness, and the moderation of personalization effects by agent's autonomy. In our mediation analysis, we focused on the relationships that showed significant effects in our linear mixed-effects regression model Appendix A.5.1: the effects of No personalization and Privacy-aware personalization on privacy concern, trust, and willingness to use; and the effects of Risk-contingent autonomy on privacy concern and trust. Because the mixed-effects regression also revealed a significant moderating effect of autonomy on personalization, we specified **a moderated mediation model** (see Figure 4). In this model, personalization (No personalization and Privacy-aware personalization, with Full personalization as reference) served as independent variables. Autonomy was dummy-coded into Risk-contingent autonomy and Full autonomy (with No autonomy as reference). Both autonomy dummies were included in the SEM to avoid collapsing Full autonomy into No autonomy, even though Full autonomy did not show significant effects in the mixed-effects regression. Autonomy was modeled both as (1) an independent variable influencing mediators and outcomes (privacy concern and trust, but not willingness to use), and (2) a moderator of the effects of personalization. The moderated-mediation SEM fit the data well: $\chi^2(1) = 0.314$, $p = 0.854$, indicating no significant misfit. The Comparative Fit Index (CFI=1.000), Standardized Root Mean Squared Residual (SRMR=0.001) and the Root Mean Square Error of Approximation (RMSEA=0.000) confirmed close fit.



Figure 4: Moderated mediation model to examine the mediation effect of users' perceived sensitivity, perceived control and perceived usefulness, and the moderation of personalization effects by agent's autonomy. Personalization (No personalization, Privacy-aware personalization; Full personalization as reference) is modeled as X, Autonomy (Risk-contingent autonomy and Full autonomy; No autonomy as reference) as W, and their interaction ($X \times W$). Perceived Sensitivity (M1), Perceived Control (M2), and Perceived Usefulness (M3) serve as mediators, with Privacy Concern, Trust, and Willingness to Use as outcomes (Y). The model tests both mediation pathways ($a \times b$) and the moderation of personalization effects by autonomy.

A.6.3 Moderated Mediation Results (RQ2)

Below, we report the detailed moderated mediation results for each of the three mediator pathways (perceived sensitivity, perceived control, and perceived usefulness) **with autonomy as the moderator**, to examine whether and how autonomy moderates the indirect effects of personalization on outcomes through each mediator.

Moderated Mediation Results for Perceived Sensitivity. Table 9 shows full moderated mediation results for the Perceived-Sensitivity pathway. First, the conditional indirect effects through perceived sensitivity are significant for both No personalization and Privacy-aware personalization across all three outcomes (privacy concern, trust, and willingness to use) under every autonomy condition, indicating that **perceived sensitivity functions as a robust mediator of personalization's effects regardless of the autonomy level**. Second, for the No personalization comparison, none of the MM indices reach significance, suggesting that autonomy does not moderate the strength of the mediation through perceived sensitivity. For Privacy-aware personalization, however, the MM_i indices for trust and willingness to use are significant, indicating that **Risk-Contingent Autonomy significantly amplifies the mediation effect through perceived sensitivity on trust and willingness to use, relative to No Autonomy**. This moderated mediation reflects a difference in mediation *strength* rather than the presence versus absence of mediation, as the indirect effects remain significant under both autonomy conditions. No significant MM_f indices are observed, suggesting that Full Autonomy does not significantly alter the mediation pathway through perceived sensitivity compared to No Autonomy.

Moderated Mediation Results for Perceived Control. Table 10 shows full moderated mediation results for the Perceived-Control pathway. First, under No Autonomy, the indirect effects through perceived control are significant for both No personalization and Privacy-aware personalization across all three outcomes (privacy concern, trust, and willingness to use), indicating that **user perceived control functions as a meaningful mediator of personalization's effects under agent's no autonomy condition**. Second, under Risk-Contingent Autonomy, these conditional indirect effects become non-significant, while the corresponding MM_i indices are significant, suggesting **a significant moderated mediation effect: Risk-Contingent Autonomy weakens the mediation pathway through perceived**

Table 9: Moderated mediation results for the **Perceived-Sensitivity** pathway, where personalization (No personalization, Privacy-aware personalization) is compared against Full personalization. Conditional indirect effects are reported under No Autonomy (baseline), Risk-Contingent Autonomy, and Full Autonomy. MM_i denotes the index of moderated mediation for Risk-Contingent Autonomy relative to No Autonomy, and MM_f denotes the corresponding index for Full Autonomy relative to No Autonomy. Significant effects (95% CI excludes 0) are in **bold**.

	No personalization			Privacy-aware personalization		
	Concern	Trust	Will.	Concern	Trust	Will.
Effects under No Autonomy [baseline]	**–.70**	**–.62**	**–.42**	**–.67**	**–.61**	**–.41**
Effects under Risk-Contingent Autonomy	**–.74**	**–.62**	**–.42**	**–.77**	**–.63**	**–.42**
Index of Moderated Mediation (MM_i)	.05	–.34	–.50	.10	**–.52**	**–.84**
Effects under Full Autonomy	**–.62**	**–.64**	**–.44**	**–.75**	**–.65**	**–.45**
Index of Moderated Mediation (MM_f)	–.12	–.10	–.17	–.08	–.14	–.22

Notes. Concern = privacy concern; Will. = willingness to use.

Table 10: Moderated mediation results for the **Perceived-Control** pathway, where personalization (No personalization, Privacy-aware personalization) is compared against Full personalization. Conditional indirect effects are reported under No Autonomy (baseline), Risk-Contingent Autonomy, and Full Autonomy. MM_i denotes the index of moderated mediation for Risk-Contingent Autonomy relative to No Autonomy, and MM_f denotes the corresponding index for Full Autonomy relative to No Autonomy. Significant effects (95% CI excludes 0) are in **bold**.

	No personalization			Privacy-aware personalization		
	Concern	Trust	Will.	Concern	Trust	Will.
Effects under No Autonomy [baseline]	**–.32**	**.42**	**.44**	**–.31**	**.42**	**.44**
Effects under Risk-Contingent Autonomy	–.06	.17	.21	–.02	.09	.15
Index of Moderated Mediation (MM_i)	**.26**	**–.25**	**–.23**	**.29**	**–.34**	**–.29**
Effects under Full Autonomy	**–.25**	.14	.15	–.19	.11	.11
Index of Moderated Mediation (MM_f)	–.07	–.28	–.29	–.12	–.31	–.33

Notes. Concern = privacy concern; Will. = willingness to use.

control relative to No Autonomy. For Full Autonomy, given that its related interaction effects did not reach significance in the linear regression, these results are reported primarily for model completeness. We therefore retained the Full Autonomy condition in the SEM, rather than merging it with No Autonomy, to more clearly present the differences across the three autonomy levels.

Moderated Mediation Results for Perceived Usefulness. Table 11 shows full moderated mediation results for the Perceived-Usefulness pathway. First, the conditional indirect effects through perceived usefulness on *privacy concern* are non-significant across all autonomy conditions for both personalization comparisons, indicating that perceived usefulness does not mediate personalization's effect on privacy concern. In contrast, the indirect effects on *trust* and *willingness to use* are significant under every autonomy condition, indicating that **perceived usefulness is a robust mediator of personalization's effects on trust and willingness to use, regardless of the autonomy level**. Second, none of the MM_i indices reach significance, suggesting that Risk-Contingent Autonomy does not significantly moderate the mediation through perceived usefulness.

Table 11: Moderated mediation results for the **Perceived-Usefulness** pathway, where personalization (No personalization, Privacy-aware personalization) is compared against Full personalization. Conditional indirect effects are reported under No Autonomy (baseline), Risk-Contingent Autonomy, and Full Autonomy. MM_i denotes the index of moderated mediation for Risk-Contingent Autonomy relative to No Autonomy, and MM_f denotes the corresponding index for Full Autonomy relative to No Autonomy. Significant effects (95% CI excludes 0) are in **bold**.

	No personalization			Privacy-aware personalization		
	Concern	Trust	Will.	Concern	Trust	Will.
Effects under No Autonomy [baseline]	–.07	**.62**	**1.29**	–.09	**.62**	**1.29**
Effects under Risk-Contingent Autonomy	–.07	**.50**	**1.01**	–.08	**.44**	**.98**
Index of Moderated Mediation (MM_i)	.01	–.14	–.28	.01	–.20	–.31
Effects under Full Autonomy	–.11	**.44**	**.97**	–.12	**.40**	**.93**
Index of Moderated Mediation (MM_f)	–.04	–.18	–.32	–.03	–.22	**-**-.36

Notes. Concern = privacy concern; Will. = willingness to use.

A.7 Supplementary for Sensitivity Detector Performance Analysis

A.7.1 Human Gold Annotation and Sensitivity Detector Performance

To evaluate the performance of the runtime sensitivity detector, two researchers manually annotated 2,250 agent-generated messages (450 participants $\times$ 5 messages each), labeling whether each message disclosed any of the sensitive items that the participant had marked as sensitive in the pre-survey. The two researchers first collectively reviewed a subset of cases to establish an initial annotation guideline. They then independently annotated another subset of cases following the guideline, calculated inter-coder agreement, and discussed disagreements to refine the guideline. After two rounds of this process, inter-coder agreement reached a high level (Cohen's $\kappa = 0.92$), and the guideline was finalized as follows.

Annotation Guideline: A message is labeled *Leaked* (1) if it discloses a participant's predefined sensitive item in any of the forms below, and *Not Leaked* (0) otherwise.

Leaked (= 1)

- **Verbatim:** the item appears in exact or near-exact wording.
- **Paraphrased:** the item is rephrased but disclosed at the same level of detail.
- **Partial:** the core fact is revealed even if minor details differ (e.g., "interview next week" to "interview tomorrow").
- **Indirect inference:** the item is not stated outright but is identifiable from the wording (e.g., "a personal matter regarding my relationship with my daughter").
- **Aggregation:** the item is not disclosed by any single message, but becomes identifiable when several messages are combined. In this case, we label the final message that completes the disclosure as leaked (1) and the earlier partial messages as not leaked (0).

Not Leaked (= 0)

- **Omitted:** no reference to the sensitive topic.
- **Generalized:** only a broad, non-identifiable category is mentioned (e.g., "hanging out with friends" for "friends who hold differing beliefs").
- **Contradicted:** the item is actively concealed (e.g., "I'm free tomorrow" despite an appointment).

- **Scenario-assigned facts:** stating a task-given value such as a nightly budget ("$200/night") is not a leak unless explicitly tied to the underlying sensitive difficulty (e.g., debt).

Following the finalized guideline, the two researchers then annotated all 2,250 messages. Using this annotation as the ground truth, we evaluated the runtime sensitivity detector (gpt-4o), which yielded 316 true positives, 1,870 true negatives, 3 false positives, and 61 false negatives (precision = .991, recall = .838, F_1 = .908, accuracy = .972). These values are reported in the first row of Table 16, alongside the additional frontier models we compared against the same gold annotation (Appendix A.7.4).

A.7.2 Robustness on the Error-Free Sample

To evaluate how these errors affect our results, we excluded all 59 participants with any runtime detector error (plus 1 with no completed response, matching the regression sample), leaving an error-free sample of N=390 (92 full-personalization, 150 no-personalization, 148 privacy-aware), and re-ran both main analyses (the linear mixed-effects models and the moderated-mediation SEM). **Overall, the key findings hold on the error-free sample: the main effects of personalization and autonomy, and the moderation of the personalization effect by risk-contingent autonomy through perceived control, are all robust to excluding participants with detector errors.**

Linear mixed-effects models on the error-free sample. Table 12 reports the models estimated on the error-free sample, the counterpart of Table 8 on the full sample. Compared with full personalization, both no personalization and privacy-aware personalization remain associated with lower privacy concern, higher trust, and higher willingness to use. Risk-contingent autonomy remains associated with lower privacy concern and higher trust, whereas full autonomy shows no significant effect on any outcome. The interaction terms retain the same attenuation pattern reported in Section 3.1.

Table 12: Linear mixed-effects models estimated on the **error-free sample** ($N = 390$), the counterpart of Table 8 on the full sample.

Effect	**Privacy Concern** Coef. (S.E.)	**Trust** Coef. (S.E.)	**Willingness to Use** Coef. (S.E.)
No personalization	-2.21*** (0.39)	0.84*** (0.24)	0.92* (0.41)
Privacy-aware personalization	-1.47*** (0.39)	0.74** (0.24)	0.98* (0.41)
Risk-contingent autonomy	-1.12* (0.44)	0.72** (0.27)	1.05* (0.47)
Full autonomy	-0.33 (0.44)	-0.08 (0.27)	-0.03 (0.47)
No personalization × Risk-contingent autonomy	2.15*** (0.56)	-0.81* (0.34)	-1.09 (0.59)
Privacy-aware personalization × Risk-contingent autonomy	0.99 (0.57)	-0.93** (0.34)	-1.39* (0.60)
No personalization × Full autonomy	0.97 (0.57)	-0.24 (0.35)	-0.41 (0.60)
Privacy-aware personalization × Full autonomy	-0.10 (0.57)	0.09 (0.35)	-0.02 (0.60)

Notes. Reference categories are full personalization and no autonomy. Standard errors in parentheses. Significance codes: *$p < .05$, **$p < .01$, ***$p < .001$.

Moderated mediation SEM on the error-free sample. We re-estimated the same SEM with 5,000 bootstrap resamples on the error-free sample. The model fits the data well: $\chi^2(2) = 1.33$, $p = .514$; CFI = 1.000; TLI = 1.016; RMSEA = 0.000; SRMR = 0.002. Consistent with the full sample, perceived control remains the pathway through which risk-contingent autonomy attenuates personalization's effects (Table 13): the conditional indirect effects are significant under no autonomy but not under risk-contingent autonomy, and all six indices of moderated mediation are significant. Risk-contingent autonomy also continues to significantly increase perceived control, which in turn reduces privacy

concern and increases trust and willingness to use, while neither perceived sensitivity nor perceived usefulness carries a significant indirect path (Table 14). The moderated mediation effects of full autonomy remain non-significant. Finally, participants under risk-contingent autonomy still showed the highest proportion of recognized privacy leakage (69.0%), above no autonomy (62.9%) and full autonomy (60.7%).

Table 13: Conditional indirect effects of personalization (compared to full personalization) on outcomes **through perceived control** on the **error-free sample** ($N = 390$), the counterpart of Table 1 on the full sample. Significant effects (95% CI excludes 0) are in **bold**.

	No personalization			Privacy-aware personalization		
	Concern	Trust	Will.	Concern	Trust	Will.
Effects under No Autonomy	**–.27**	**.25**	**.27**	**–.26**	**.24**	**.26**
Effects under Risk-Contingent Autonomy	.03	–.02	–.03	.10	–.09	–.09
Index of Moderated Mediation	**.30**	**–.27**	**–.30**	**.36**	**–.33**	**–.35**

Notes. Concern = privacy concern; Will. = willingness to use.

Table 14: Effects of risk-contingent autonomy (IA) (compared to no autonomy) on mediators (M) and indirect paths to outcomes on the **error-free sample** ($N = 390$), the counterpart of Table 2 on the full sample. Significant effects (95% CI excludes 0) are in **bold**.

	$IA \rightarrow M$	$IA \rightarrow M \rightarrow$Concern	$IA \rightarrow M \rightarrow$Trust	$IA \rightarrow M \rightarrow$Will.
Perceived sensitivity (M1)	.06 [-.17, .29]	.08 [-.23, .40]	-.03 [-.16, .09]	-.02 [-.12, .07]
Perceived control (M2)	**.62** [.15, 1.08]	**-.26** [-.55, -.05]	**.24** [.06, .44]	**.26** [.06, .53]
Perceived usefulness (M3)	.47 [-.00, .95]	-.10 [-.29, .01]	.30 [-.00, .61]	.63 [-.00, 1.28]
Direct (c')	–	**-1.19** [-2.04, -.32]	.31 [-.03, .65]	n/a

Notes. Concern = privacy concern; Will. = willingness to use. The direct path from IA to willingness to use is not included (n/a), as no significant main effect was found in the mixed-effects model.

A.7.3 How Sensitivity Detector Errors Relate to User Perception

We further exploratorily examined how sensitivity detector errors relate to participants' perceptions.

Over-reminders (false positives). Only three participants experienced an over-reminder, and they were all in different conditions (Privacy-aware & no autonomy; Full personalization & risk-contingent autonomy; Full personalization & full autonomy). The sample size is too small to draw statistically meaningful conclusions, and no consistent pattern was observed.

Missed reminders (false negatives). Missed reminders could arise only under full personalization, because the agent had no access to user-labeled sensitive items in the other two personalization conditions. In total, 61 missed reminders affected 56 of the 150 full-personalization participants: 16 messages affecting 15 participants under no autonomy, 24 messages affecting 21 participants under risk-contingent autonomy, and 21 messages affecting 20 participants under full autonomy. Each condition cell contains 50 participants and 250 checked agent messages (50 participants $\times$ 5 messages).

Within full personalization, we compared participants who experienced at least one missed reminder ($n = 56$) with those whose disclosures were all caught ($n = 92$), excluding the two participants who also saw an over-reminder. We modeled each perception measure with a linear mixed model, `measure ~ missed + (1 | scenario)`, in which the coefficient on `missed` is the adjusted mean difference (missed minus caught). **Pooled across autonomy levels, a missed disclosure is associated with significantly lower trust (Coef.** $= -0.58$**,** $p = .012$**, Cohen's** $d = -0.42$**), while the other measures trend lower without reaching significance** (Table 15).

Table 15: Adjusted mean differences between participants whose disclosure was missed by the detector ($n = 56$) and those whose disclosures were all caught ($n = 92$), within the full personalization condition.

Perception measure	Coef. (missed − caught)	p	Cohen's d
Privacy concern (1–7)	-0.05	.880	-0.03
Trust (1–7)	**-0.58**	**.012**	-0.42
Willingness to use (1–7)	-0.61	.080	-0.30
Perceived sensitivity (0/1)	-0.03	.685	-0.07
Perceived control (1–5)	-0.34	.069	-0.31
Perceived usefulness (1–5)	-0.17	.326	-0.17

Notes. Coefficients from linear mixed models with a random intercept for *scenario*. Significant effects ($p < .05$) are in **bold**.

A.7.4 Detector Performance Across Frontier Models

To examine how detector performance depends on the underlying model, we re-ran the runtime detector with five additional frontier models, scoring each against the same human gold annotation on all 2,250 agent-generated messages (Table 16).

The models differ mainly in how they trade off precision against recall, rather than in whether the detection task is feasible. The gpt-4o detector used in our study favors precision (.991) over recall (.838): it rarely over-reminds but misses more disclosures, and as reported in Appendix A.7.3, such missed reminders are associated with lower trust. GPT-5.5 sits at the opposite extreme (recall = .981, precision = .777): it rarely misses a disclosure but over-reminds far more often. The remaining models fall in between and reach the highest F_1 scores, up to .940 for Claude Opus 4.8.

We are nonetheless cautious about concluding that the higher-recall models move detection in a strictly safer direction. A low-precision detector hands control back to users even when it is unnecessary, and our comparison between no autonomy and risk-contingent autonomy suggests that such excessive interruptions carry their own cost. Because the effect of over-reminding on user perception remains under-studied, and our own data contain too few false positives to estimate it, we do not declare a net direction and treat this as an important direction for future work.

One practical signal is that DeepSeek V4 Flash, a smaller open-source model, reaches performance comparable to the larger proprietary models (precision = .896, recall = .958). This suggests that the sensitivity detection module could be deployed locally, letting users benefit from runtime leak detection without routing their personal information to a third-party provider.

Table 16: Performance of the runtime sensitivity detector across frontier models, each scored against the same human gold annotation on all 2,250 agent-generated messages.

Detector model	TP	TN	FP	FN	Precision	Recall	F_1	Accuracy
gpt-4o (used in our study)	316	1,870	3	61	**.991**	.838	.908	.972
GPT-5.5	370	1,767	106	7	.777	**.981**	.868	.950
Claude Opus 4.8	358	1,846	27	19	.930	.950	**.940**	**.980**
Gemini 3.5 Flash	357	1,845	28	20	.927	.947	.937	.979
DeepSeek V4 Pro	348	1,840	33	29	.913	.923	.918	.972
DeepSeek V4 Flash	361	1,831	42	16	.896	.958	.926	.974

Notes. TP: true positive, TN: true negative, FP: false positive (over-reminder), FN: false negative (missed reminder). The best value in each metric column is in **bold**.