MET: Theory-Grounded and Culture-Aware Multilingual Moral Reasoning

Ayoung Lee[1], **Ryan Kwon**[1], **Yunxiang Zhang**[1], **Yuxuan Liu**[1], **Peter Railton**[2], **Lu Wang**[1]
[1]Department of Computer Science and Engineering
[2]Department of Philosophy
University of Michigan
Ann Arbor, MI, USA
{leeay, ryankwon, yunxiang, yuxualiu, prailton, wangluxy}@umich.edu

🤗 huggingface.co/collections/launch/met github.com/aylee2008/met

Abstract

Language models are increasingly used for moral decision-making across diverse linguistic and cultural contexts, yet existing work overlooks multilinguality on three aspects: 1) multilingual evaluation benchmarks use direct translation, failing to adapt culture-specific items; 2) inference-time methods for moral reasoning rely on static, English-centric scaffolds and lack grounding in moral theory; 3) training methods for moral decision-making typically require expensive supervision from stronger models or human annotators. We address these gaps with three contributions. First, we introduce MCLASH, a multilingual moral decision-making benchmark to capture culturally situated moral intuitions and social norms across languages. Second, we propose MET (**M**ultilingual **E**thics with **T**heory-grounded reasoning), a two-step prompting method built on expert-curated, theory-based grounds drawn from psychology and philosophy: the model first selects situation- and culture-specific grounds, then reasons over them in the native language of the user. Third, we introduce MET-D (MET-Distillation), which enhances the second step through a self-distillation training stage that requires no external supervision. MET-D improves macro-F1 over the base model on all three models of different sizes and families (Qwen3-4B, Qwen3-8B, Gemma3-4B), by an average of 3.71 points on MCLASH and 4.23 on MMoralExceptQA, with a peak MCLASH gain of 12.94 points for Malay on Qwen3-8B. We further reveal that MET-D increases native-language reasoning by 62.13 points on average, and that beneficial grounds differ systematically across cultures. Together, these contributions open the path for culture-aligned, theory-grounded multilingual moral reasoning.

1 Introduction

Language models are increasingly deployed in moral decision-making across high-stakes domains such as law (Xiao et al., 2021; Nguyen, 2023) and healthcare (Singhal et al., 2023; Hu et al., 2024), where users span diverse cultural backgrounds. Effective deployment in such settings requires that models reason within the linguistic and cultural context of the user, accounting for the local value systems that shape a sound moral judgment. However, culturally aligned moral decision-making remains overlooked in both evaluation and methods.

Evaluation: direct translation strips cultural context from moral dilemmas. Existing multilingual moral benchmarks directly translate English scenarios (Kumar & Jurgens, 2025; Farid et al., 2025) without adapting culture-specific items (Newmark, 1988) such as named entities, institutions, currencies, and customs. When directly translated into Korean or Hindi, a U.S. scenario set during "Thanksgiving" or at a "Wendy's" can import improper

: Dimensions : Grounds : Descriptions

English

Normative Authority
- **Truth-based Authority**: Ground your reasoning in the assumption that there are objective moral principles or values. Justify your conclusion by appealing to principles that would be true independently of cultural agreement or personal preference.
- **Reason-Based Authority**: Ground your reasoning in principles or values that any rational agent would be committed to. Emphasize logical consistency, universalizability, and coherence.

Value Systems
- **Moral Foundations Theory**: Identify which moral foundations are most relevant in this case (e.g., care/harm, fairness/cheating, loyalty/betrayal, authority/subversion, sanctity/degradation, liberty/oppression). Frame your reasoning around the protection or violation of these foundations.
- **Schwartz's Value System**: ...

Ethical Theories
- **Deontology**: ...
- **Utilitarianism**: ...

Cognitive Reasoning Strategies
- **Step-by-step reasoning**: ...
- **First-principles reasoning**: ...

Conflict Handling Strategies
- **Context-Sensitive Resolution**: ...

Moral Uncertainty
- **Probablistic Moral Uncertainty**: ...
- **Maximin Reasoning**: ...

Korean (Translated into English)

Normative Authority
- **Truth-based Authority**: Ground your reasoning in the assumption that there are objective moral principles or values. Justify your conclusion by appealing to principles that would be true independently of cultural agreement or personal preference.
- **Reason-Based Authority**: Ground your reasoning in principles or values that any rational agent would be committed to. Emphasize logical consistency, universalizability, and coherence.

Value Systems
- **Moral Foundations Theory**: Identify which moral foundations are most relevant in this case (e.g., care/harm, fairness/cheating, loyalty/betrayal, authority/subversion, sanctity/degradation, liberty/oppression). Frame your reasoning around the protection or violation of these foundations.
- **Schwartz's Value System**: ...
- **Hofstede's Cultural Dimensions**: ...

Ethical Theories
- **Deontology**: ...
- **Utilitarianism**: ...
- **Contractarianism**: ...

Cognitive Reasoning Strategies
- **Step-by-step reasoning**: ...
- **Counterfactual reasoning**: ...

Conflict Handling Strategies
- **Context-Sensitive Resolution**: ...

Figure 1: **Example ground selection in different languages**: Grounds are organized into dimensions and paired with descriptions. For the same situation, the selected grounds vary by language: in English, First-principles reasoning reflects the Western rationalism, whereas in Korean, Contractarianism reflects Confucian values.

Western cultural context into account. We address this with MCLASH, a multilingual moral decision-making benchmark built by culturally adapting CLASH (Lee et al., 2025)—a corpus of long-form high-stakes scenarios paired with character descriptions—into five additional languages (Chinese, Hindi, Korean, Malay, Spanish). Adaptation is performed by Qwen3-32B (Yang et al., 2025) and then inspected by native speakers, yielding 1,852 situations and 9,260 character descriptions.

Method (inference): existing scaffolds lack theory grounding, culture- and situation-specific adaptation, and multilingual support. Beyond producing the correct decision, the reasoning that justifies it must be reliable and understandable for users to audit (Gilpin et al., 2018; Besold & Uckelman, 2018). Theoretical grounding can improve reasoning quality in moral decision-making (Chakraborty et al., 2025), yet most existing methods do not engage with moral theories such as deontology or care ethics (Jin et al., 2022; AlKhamissi et al., 2024). Even the theory-grounded work (Chakraborty et al., 2025) covers only a narrow set of theories and applies them without cultural or situational adaptation. Research on moral reasoning is also largely English-only; methods are developed and evaluated on English benchmarks (Chiu et al., 2025), and multilingual reasoning techniques borrowed from culture-agnostic tasks assume a language-invariant reasoning structure (Zhang et al., 2025; Zhu et al., 2024; She et al., 2024; Zhao et al., 2025; Yoon et al., 2024), which does not hold when moral frameworks vary by culture.

We address these gaps with MET (**M**ultilingual **E**thics with **T**heory-grounded reasoning), a two-step prompting method in which the model first selects the grounds most relevant to the given situation, then uses them to produce a grounded reasoning chain in the native language of the user (Figure 1). The full, multilingual set of grounds from which the model selects is developed by the authors including a domain expert[1], drawing on psychology and philosophy literature, and organized into six high-level dimensions (e.g., Value Systems, Conflict Handling Strategies).

Method (training): training the model to ground its reasoning in moral theory suffers from a lack of verifiable signals. Prompting alone is insufficient: even when the model selects relevant grounds, the reasoning chain frequently engages with only a few (Figure 2), leaving the rest unaddressed and producing shallow, one-sided judgments. However, training the model to substantively engage with the grounds is hard because moral decision-making is subjective and generally lacks the verifiable ground truth that enables rejection sampling (Shao et al., 2024; Guo et al., 2025); existing methods therefore rely on distillation

[1]One of the authors, Peter Railton, is a professor of ethics, value theory, and moral psychology.

Situation. When off-duty firefighters in North Bend, Oregon, cut down 25 alder trees in February, Fire Chief Scott Graham said he thought the firefighters could take the wood, and he could help himself to some as well. But the Oregon Government Ethics Commission has reprimanded Graham, saying he should have known he could not take the wood for personal use... Chief Graham said the whole episode "basically boiled down to miscommunication."

Character. Someone who deeply values the principles of ethical conduct within public service ... feels that forgiveness is crucial when dealing with honest mistakes and miscommunications, seeing these moments as opportunities for growth...

Question. Is punishing Graham morally acceptable from the character's perspective?

Ten grounds selected. Institution-Based Responsibility-Based Moral Foundations Right-Based Deontology Harm–Benefit Stakeholder Principle-Based Context-Sensitive Multi-framework .

Reasoning. "... The Oregon Government Ethics Commission's reprimand aligns with the need to uphold ethical standards... This aligns with both institutional legitimacy (normative authority) and the principle of responsibility-based accountability. The action of punishing Graham is justified as a necessary step to maintain ethical standards..."

Figure 2: **Sparse *theory-guided reasoning* behavior in the base model.** On `26-scug` (English), the base explicitly mentions only two of its ten grounds, Institution-Based and Responsibility-Based , both weighing the duty to uphold ethics standards, and collapses to a definitive `yes` (punish) rather than the correct `ambiguous`, under-weighting the character's equal commitment to forgiving an honest miscommunication.

from stronger models or extensive human involvement (Tennant et al., 2025; An & Du, 2026; Feng et al., 2025). We sidestep this by constructing a synthetic dataset that follows the structure of CLASH: each dilemma is paired with a character whose value priorities make the correct decision automatically verifiable. MET-D (MET-Distillation) then applies rejection-sampling *self-distillation* on this dataset, using correct decisions as a proxy for substantive engagement with the grounds.

On MCLASH, MET-D improves the average F1 score by 3.71 points over the base model across three models spanning different sizes and families (Qwen3-4B, Qwen3-8B, and Gemma3-4B), with the largest single gain of 12.94 points for Malay on Qwen3-8B. These improvements generalize to other datasets, reaching 4.23 points on average for MMoralExceptQA(Jin et al., 2022) and 3.53 points for MoCa(Nie et al., 2023) on Qwen3-4B. Beyond performance, MET-D increases native-language reasoning by 62.13 percentage points on Qwen3-4B, making the reasoning more legible for non-English speakers. We further find that the most beneficial grounds for each culture align with its actual cultural characteristics, and that cross-lingual transfer follows linguistic typology rather than cultural similarity.

Our contributions are summarized as follows:

- **MCLASH**, a multilingual moral decision-making benchmark of 1,852 long-form scenarios across six languages, constructed by cultural adaptation rather than direct translation.
- **Expert-curated theoretical grounds** for moral reasoning, organized into six high-level dimensions and translated into all six languages.
- **MET**, a two-step prompting method that employs situation- and culture-specific grounds, and **MET-D**, which extends MET with a self-distillation training stage that requires no external supervision.

2 Related Work

2.1 Moral Decision-Making Datasets

Most previous work in moral decision-making either probes the preferences of the models rather than providing an answer, which makes it hard to assess their actual decision-making

ability (Chiu et al., 2024; Samway et al., 2025; Wu et al., 2025a;b), or does not consider multilinguality, thereby overlooking the cultural differences in making judgments (Lee et al., 2025; Scherrer et al., 2024; Nie et al., 2023). Some recent studies incorporate multilinguality, but their scenarios are either short, fewer than three sentences, which limits their narrative complexity (Farid et al., 2025; Pistilli et al., 2024), or rely on direct translation (Farid et al., 2025; Jin et al.) without accounting for cultural adaptation. We address these gaps by introducing a new multilingual dataset, MCLASH, that includes culturally-adapted long scenarios.

2.2 Inference-Time Methods for Moral Decision-Making

Most inference-time methods for moral decision-making rely on structured prompting (AlKhamissi et al., 2024; Jin et al., 2022; Chakraborty et al., 2025), but apply the same framework to every dilemma. This approach is insufficient, since the appropriate moral framework varies with the context of each dilemma (Fletcher, 1966; Dancy, 2004). In contrast, MoReBench (Chiu et al., 2025) addresses per-instance adaptation through rubrics for evaluating moral reasoning. While the rubrics can be adapted as inference-time guidance, they are coarse, atheoretical, English-only, and labor-intensive to construct. Closest to our approach, Chakraborty et al. (2025) shows that theoretical scaffolds improve reasoning quality, but uses a narrow, static, and English-only set of theories. MET combines theory grounding with multilingual support and per-instance, per-language adaptation, enabling culture-aligned reasoning in the native language of the end user.

2.3 Multilingual Training for Moral Decision-Making

Methods developed for conventional reasoning domains such as math and code treat non-English reasoning as a translation of English reasoning, which assumes the same reasoning structure across languages. Common techniques include aligning non-English representations toward the English subspace (Zhang et al., 2025), optimizing for similarity between non-English and English reasoning chains (She et al., 2024), and bridging multilingual encoders with English-trained reasoners that apply English reasoning patterns to inputs in any language (Zhao et al., 2025; Yoon et al., 2024). These approaches fail in moral decision-making, where different cultures apply different moral frameworks reflecting their distinct values (Hwang et al., 2025; Myung et al., 2024).

Existing training methods for moral reasoning rely on heavy external supervision via hand-crafted rewards (Tennant et al., 2025) or stronger models (An & Du, 2026), and operate only in English. In the multilingual space, prior work is largely evaluation-focused (Agarwal et al., 2024; Kumar & Jurgens, 2025; Zhou et al., 2025), and training methods target cultural commonsense rather than reasoning through moral dilemmas where values conflict, using cultural surveys (Li et al., 2024a), multi-agent debates (Li et al., 2024b), fine-grained critique (Feng et al., 2025), or culture-aware self-improvement (Xu et al., 2025). MET-D directly targets moral decision-making and self-supervises via the character-paired structure of CLASH.

3 Construction of MCLASH

CLASH (Lee et al., 2025) consists of 345 high-stakes situations paired with 3,795 character descriptions, and tasks models with making a decision from the perspective of the character. We adapt the original English situations into five languages (Chinese, Hindi, Korean, Malay, and Spanish) and their corresponding cultures[2] using Qwen3-32B (Yang et al., 2025), selected for its adaptation quality (Appendix A.1). Next, native speakers review and modify the narratives with a rigorous checklist (Figure 11) to ensure cultural relevance. When a situation seems entirely irrelevant to a given culture, we discuss with the inspectors and discard

[2]Cultural boundaries are inherently dynamic and uncertain (Delanoy, 2020), and can be defined by various criteria such as religion, geography, or language. Following common practice in cross-cultural NLP (Naous et al., 2024; Maji et al., 2025; Onohara et al., 2025), we use language as a proxy for culture and consider all regions where each language is spoken.

it if necessary. We then adapt the character descriptions based on the adapted situations, followed by an additional round of human inspection.

Importantly, this process does not involve direct translation, a limitation of previous work. Instead, we carefully adapt each instance to preserve culturally specific nuances. For example, instead of directly translating "Amazon", the American big-tech company, we instruct the inspectors to adapt it to other big-tech companies in their culture, such as "Naver" and "Kakao" in Korea. We refer to the resulting dataset as MCLASH, which consists of 1,852 situations and 9,260 character descriptions. Details of adaptation, human inspection, and data statistics are presented in Appendices A.2 and A.3.

4 Method

In §4.1, we describe how we curate the theoretical grounds. We then present 1) MET, our two-step prompting method of selecting and applying the grounds, and 2) MET-D, which constructs a training dataset and adds a rejection-sampling distillation stage on top of MET in §4.2.

4.1 Theoretical Grounds

In collaboration with a domain expert, we curate a global set of theoretical grounds, translated into all six languages, for the model to select from. A total of 37 grounds are organized into six dimensions, each paired with a description that helps the model understand the ground and select the most relevant ones. This uniform structure makes the set easy to extend: a new ground can be added simply by specifying its dimension and description without changing the selection process. Figure 1 shows an example of these grounds and their dimensions.

We explain each dimension below, with the full list of grounds and descriptions provided in Appendix B.1. The **Normative Authority** dimension (e.g., Railton, 1986; Wood, 2008; Reus-Smit et al., 2005) establishes the foundational premises for the reasoning process, while **Value Systems** (e.g., Graham et al., 2013; Schwartz, 2012) identify the values that should be taken into account. **Ethical Theories** (e.g., Alexander & Moore, 2007; Mill, 2016) provide the normative structure guiding the reasoning, and **Cognitive Reasoning Strategies** (e.g., Wei et al., 2022; Freeman, 2010) outline its underlying cognitive structure. Finally, **Conflict Handling Strategies** (e.g., Dancy, 2001; Musschenga, 2005) and **Moral Uncertainty** (e.g., Ess, 2006; MacAskill et al., 2020) address approaches for navigating dilemmas and managing uncertainty in moral decision-making.

4.2 Guiding Reasoning using Grounds

MET. Given a situation, MET guides the target model in two steps (Figure 3): 1) *Ground Selection*: The model is prompted with the dimensions, grounds, and descriptions, and asked to select the grounds most relevant to the given situation, forming an instance-specific framework. 2) *Theory-Guided Reasoning*: Given the selected grounds and the situation, the model outputs the reasoning and the answer. The prompts are presented in Figures 14 to 16.

MET-D. Analysis of the initial results reveals that in the second step, models often engage with only a subset of the grounds they select, leaving the rest unaddressed, thus producing shallow reasoning (Figure 2). To enhance the utilization of the selected grounds in *theory-guided reasoning*, we introduce additional training using a synthetic dataset that follows the structure of CLASH. We refer to this training procedure, along with the subsequent MET prompting, as MET-D (MET-Distillation). Moral dilemmas typically require human annotation for ground-truth answers, especially "ambiguous" ones. CLASH circumvents this by pairing each situation with well-defined character descriptions whose value priorities determine the ground-truth decision, eliminating the need for human supervision. CLASH also captures moral ambivalence through ternary labels (`yes`/`no`/`ambiguous`) rather than clear-cut `yes`/`no`.

The training dataset is constructed as follows. We first derive a comprehensive cultural value set by extracting relevant values from the WVS questionnaire (WVS, 2023-02-17;



Figure 3: **Method**: In MET, the model first selects situation- and language-specific grounds, then reasons based on them. MET-D extends this by adding a self-distillation training stage to improve *theory-guided reasoning*. The training dataset for MET-D is synthetically generated using Qwen3-32B, following a situation-and-character-description structure where ground-truth labels are automatically derivable without manual annotation.

Sheetal et al., 2025) using multiple models (Qwen3-32B and GPT-oss-120B), then taking the union of the resulting value sets, with the prompt used for extraction presented in Figure 17. For each dilemma, we randomly sample three values from the constructed value set per side and prompt Qwen3-32B to generate a corresponding scenario. We then follow the prompts used in CLASH to generate five character descriptions per scenario, each associated with a `yes`, `no`, or `ambiguous` ground-truth decision. We generate 500 scenarios and 2,500 character descriptions per language. To ensure topic diversity, each dilemma is additionally conditioned on one of six high-stakes topics (Government, Medical, Business, Journalism, Education, and Technology), equally distributed across generated scenarios.

Using this dataset, we prompt the target model M to select grounds and generate corresponding reasoning chains for decision-making. Through rejection sampling, we only retain instances where the final answer of the model matches the ground truth, and balance them so that `yes`/`no`/`ambiguous` appear in a 1:1:1 ratio and the number of training instances is equal across languages. These filtered reasoning chains are used to train M. Finally, we reapply the two-step prompting procedure, using the base model for *ground selection* and the trained model for *theory-guided reasoning*.

5 Main Results

We evaluate on three target models spanning different sizes and families: Qwen3-4B, Qwen3-8B, and Gemma3-4B. Unless a model is explicitly named, all results and analyses use Qwen3-4B, our default model, chosen for its multilingual capabilities and inspectable internal reasoning chains. For evaluation, we use our curated benchmark MCLASH alongside two additional datasets: MMoralExceptQA (Farid et al., 2025), a multilingual translation of MoralExceptQA (Jin et al., 2022) where the correct decision is always clear-cut (`yes` or `no`), and MoCa (Nie et al., 2023), an English-only dataset with ternary labels (`yes`, `no`, `ambiguous`). Together, these datasets allow us to assess the generalizability of our approach across multilingual and non-clear-cut moral decision-making scenarios. Both prompts for *ground selection* and *theory-guided reasoning* are presented in the language of each test instance, and following (Tam et al., 2025), the internal reasoning chains are enforced in the native language using native-language prefill tokens right after the thinking token `<think>`, equivalent to

	Qwen3-4B			Qwen3-8B			Gemma3-4B		
Dataset	**Base**	**MET**	**MET-D**	**Base**	**MET**	**MET-D**	**Base**	**MET**	**MET-D**
MMoralExceptQA									
High	65.57	**71.35**	71.03	64.10	62.16	**69.23**	64.62	65.87	**68.57**
Low	55.17	54.26	**59.46**	53.35	54.56	**55.44**	51.89	52.33	**57.90**
All	62.97	67.08	**68.14**	61.42	60.26	**65.79**	61.27	61.16	**64.42**
MCLASH									
High	64.17	64.62	**67.67**	68.62	69.80	**71.84**	66.70	61.77	**69.06**
Low	53.44	52.87	**57.93**	52.77	52.78	**56.24**	55.19	52.44	**60.44**
All	58.81	58.75	**62.80**	60.70	61.29	**64.04**	60.95	57.11	**64.75**
MoCa	44.07	42.43	**47.60**	43.53	42.73	**44.90**	**40.03**	33.60	34.97
Avg	55.28	56.09	**59.51**	55.22	54.76	**58.24**	54.08	50.62	**54.71**

Table 1: **Main results**: Macro F1 averaged across languages, grouped by resource level (High: en, zh, es; Low: ko, hi, ms). Blue and red mark gains and drops over Base, and **bold** indicates the best per row per model. MET-D improves over Base on all three models with the only exception being Gemma3-4B on MoCa.

`Okay`, such as `Primero` for Spanish. This reflects the natural setting in which non-English speakers will interact with the model, and makes the reasoning process more transparent to them rather than only the final answer.

Table 1 presents the main results, with the full per-language results for all models provided in Appendix C.1. **1) Prompting alone is unreliable, but training fixes this.** MET improves over Base on Qwen3-4B (+0.81) but degrades on Qwen3-8B (-0.46) and Gemma3-4B (-3.46); adding training (MET-D) closes this gap, yielding consistent gains over Base on all three models (+4.23, +3.02, +0.63). **2) Our method works on both high- and low-resource languages.** Especially on MCLASH, it helps low-resource languages more, with a consistently larger gain from MET-D across all three models (e.g., +4.49 vs. +3.50 on Qwen3-4B, +5.25 vs. +2.36 on Gemma3-4B). **3) Gains generalize across clear-cut (MMoralExceptQA) and ambiguous (MoCa) datasets.** The only exception is Gemma3-4B on MoCa. After inspecting the model outputs, we find that MET-D makes Gemma3-4B on MoCa more inclined toward clear-cut (`yes`/`no`) answers, causing a drop in `ambiguous` F1.

We also present an ablation study to show where training helps. We experiment with three settings (Table 2): (1) no grounds, with the trained model generating answers directly, (2) the trained model for both selection and following, (3) and the base model for *ground selection* paired with the trained model for *theory-guided reasoning*. Comparing (2) and (3), we observe that replacing the base selector with the trained one performs worse, indicating that our *theory-guided reasoning*-focused training does not transfer positively to *ground selection*. We therefore use the base model for *ground selection* as our default and leave training *ground selection* to future work. The comparison between (1) and (3) further shows that theory-grounded prompting remains beneficial after training, outperforming direct answering without the grounds.

Selection	Base	None	Trained	Base
Reasoning	Base	Trained	Trained	Trained
High-resource				
English	70.97	73.98	**74.49**	73.75
Spanish	63.70	64.50	65.00	**67.00**
Chinese	59.21	60.93	60.98	**62.26**
Low-resource				
Korean	50.38	**58.26**	56.72	57.88
Hindi	47.10	45.30	49.61	**50.45**
Malay	61.13	65.24	64.67	**65.45**
Overall avg	58.75	61.37	61.91	**62.80**

Table 2: **Ablation Study**: Each column pairs a model choice for **Selection** (*ground selection*) and **Reasoning** (*theory-guided reasoning*). MET-D shows the best performance, indicating that the trained model mainly improves *theory-guided reasoning* but not *ground selection*. The best results per row are indicated in **bold**.

6 Analyses

We examine why our method works and what it reveals about multilingual moral reasoning. We first verify that *ground selection* captures relevant grounds instead of random noise (§6.1), then show that training increases engagement with the selected grounds (§6.2). We also analyze how beneficial grounds differ across languages (§6.3). We further show that training improves not only performance but also legibility, by raising the proportion of native-language reasoning (§6.4), and finally analyze cross-lingual transfer (§6.5).

6.1 Selection Captures Relevant Grounds

We confirm that *ground selection* selects relevant grounds rather than noise along two axes: performance comparison against a random-selection baseline, and the stability of the selected grounds measured by Cohen's κ across random seeds (within model) and across target models. As shown in Table 3, our selection outperforms random selection across both high- and low-resource languages, with a larger gain in low-resource settings (+2.03). Cohen's κ is 0.468 within model and 0.259 across models. Considering the inherent ambiguity of the task, the level of agreement indicates that the selection reflects systematic, non-random patterns.

Selection	High	Low	Avg
Random	66.65	55.90	61.28
Qwen3-4B	**67.67**	**57.93**	**62.80**

Table 3: **Effect of ground selection**: Model-based selection outperforms random.

6.2 Training Increases Utilization of the Selected Grounds

We validate that training leads to improved utilization of selected grounds in *theory-guided reasoning*. We sample 20 instances in English, Chinese, and Hindi and have annotators mark whether each selected ground is used in the reasoning of Qwen3-4B both before and after training. The per-instance utilization rate is the fraction of selected grounds used. Average utilization increases from 52.10% to 61.19% in English, from 31.87% to 37.05% in Chinese, and from 42.00% to 51.75% in Hindi.

However, we note that this metric primarily captures *engagement*, which refers to whether the reasoning mentions and applies the given grounds. This is different from reconciliation, which involves weighing and integrating these grounds to reach a conclusion. We observe cases where the number of mentioned grounds increases but reconciliation is absent (Figure 18). Improving how models reconcile grounds is left to future work.

6.3 Beneficial Grounds are Different per Language

For each ground, we filter the instances where the ground is selected in *ground selection* and compute the macro-F1 of our trained model on those instances with and without the grounds included in the prompt for generating the reasoning chain. The difference between the two F1 scores quantifies how much each ground contributes to the performance. Figure 4 reports the mean F1 gain per dimension and the top-six beneficial grounds per language.

Every dimension yields a positive average gain with variance across languages. Hindi benefits the most broadly, likely because its low-resource status leaves the base model with weaker structural priors for Hindi moral reasoning. The **Moral Uncertainty** dimension shows cultural friction: it hurts F1 in Korean and Chinese, consistent with the Confucian emphasis on relational obligations that prescribe a definite moral stance.

The top-six grounds per language further reveal culturally-grounded differences. English gains most from Probabilistic Moral Uncertainty (+9.6), First-principles reasoning (+9.0), and Maximin Reasoning (+4.9), representing the Enlightenment rationalism of the Anglo-American discourse, also known as the *Analytic Philosophy* (Glock, 2013). Spanish is led by Relation-Based Authority (+11.8), consistent with the interpersonal interdependency at the core of Latin *familismo* (Lopez et al., 2022). Korean and Chinese both benefit substantially from Contractarianism, aligning with their Confucian focus in which obligations are understood as mutually-held relational contracts.



Figure 4: **Gain per dimension and ground**: All dimensions yield positive gains on average, with language-specific nuances. Hindi benefits most, likely because the base model has less prior knowledge of moral reasoning in low-resource languages.



Figure 5: **Native-language reasoning**: MET-D achieves the highest average F1 and native-language percentage in reasoning chains, with the only exceptions being Hindi F1 (a low-resource language) and Chinese F1 and native percentage (where the base model already reasons natively without enforcement).

Together, these results show that beneficial grounds are not language-agnostic: they track real cultural patterns, underscoring the importance of considering multilinguality carefully rather than simply translating English reasoning.

6.4 Training Improves Native-Language Reasoning

Since native speakers naturally prompt models in their native language and expect responses in the same language, we fix both the input and output language to the native language as our default setting. Beyond input and output, we additionally enforce the internal reasoning chain to be in the native language, motivated by legibility: end users can audit the model's reasoning process only if it is in a language they understand.

A natural question to pose is whether using native-language reasoning hurts task performance. To answer this, we use MCLASH to compare four conditions that share the same input/output language setting but differ in how the internal reasoning chain is handled: 1) base model (Qwen3-4B) with no language enforcement on reasoning chains, 2) base model with explicit prefill tokens to enforce native-language reasoning, 3) our trained model plus prompting without enforcement, and 4) our full method, MET-D, with training, prompting, and enforcement. We compare the performance and the percentage of the native language. We use word-level language detection for non-Latin languages, where the unicode scripts uniquely identify the language, and sentence-level language detection for Latin languages, where per-word detection is unreliable.

Figure 5 reveals a clear pattern, with full numbers presented in Table 8. Enforcing native-language reasoning via prompting alone hurts performance on average (-2.17) as shown in (a). Without training, the base model lacks genuine multilingual reasoning ability, so forcing it to reason in a non-dominant language degrades output quality. Native-language reasoning is thus a trade-off: legibility at the cost of performance.

Our training breaks the trade-off, improving both performance and legibility simultaneously. Even without explicit enforcement, the trained model already reasons predominantly in the native language (from $<1\%$ to $\approx 90\%$ across languages) and outperforms the non-enforced base model by $+1.23$ F1 percentage points. Furthermore, combining training with enforcement yields a gain of $+2.02$ points, demonstrating that MET-D achieves high-quality native-language reasoning, enhancing both legibility and performance, although some per-language exceptions emerge: for Hindi, the non-enforced base setting shows the highest F1, due to Hindi's low-resource nature; for Chinese, the same setting shows the highest native-language percentage, as Qwen3-4B already reasons natively in Chinese without explicit enforcement.

6.5 Cross-Lingual Transfer Reflects Typology

Even without target-language training, cross-lingual transfer can still help. We train Qwen3-4B on each language individually and evaluate on all six (Figure 6). **1) Linguistic similarity drives transfer; cultural similarity does not.** The two SOV languages (Korean and Hindi) each improve the other's F1 by 2.1 points. SVO Latin-script languages (English, Spanish, Malay) likewise show positive mutual transfer, while Chinese, though SVO, uses a different script and breaks this pattern. In contrast, culturally similar languages Chinese and Korean, both from the Confucian sphere, show only weak transfer (zh→ko $+0.8$, ko→zh -0.4). **2) Training on high-resource languages is not always helpful.** For some high-resource targets (English, Chinese), training on the target language itself hurts its evaluation while training on a different language helps. This suggests that single-language training can reinforce cultural biases in *theory-guided reasoning*, while multilingual exposure mitigates them. This is a domain-specific characteristic of multilingual moral reasoning, since prior findings in other domains suggest that multilingual mixing typically degrades performance (Arivazhagan et al., 2019; Blevins et al., 2024). **3) Korean is a notable outlier.** Korean shows an unusually high own-language gain ($+9.8$ points), which we attribute to its typological isolation: a unique Hangul script and honorific system, making same-language training the most effective path to improvement.



Figure 6: **Cross-lingual transfer**: Linguistic similarity improves transfer. For some high-resource languages (English, Chinese), training on the language itself hurts performance, while training on a different language helps.

7 Conclusion

We curate a culturally adapted evaluation dataset and propose a method that grounds moral reasoning in psychological and philosophical theories. We carefully curate dimensions and theory-relevant grounds, then introduce a two-step process consisting of *ground selection* followed by *theory-guided reasoning*. In addition, we present a self-distillation training strategy designed to improve the ability of models to adhere to the grounds during reasoning. Our results demonstrate an average F1 improvement of 3.71 points on MCLASH and 4.23 points on MMoralExceptQA, along with enhanced legibility, reflected in an increase in native-language usage of 62.13 percentage points. We further find that beneficial grounds align with the actual characteristics of each culture, while cross-lingual transfer follows linguistic typology rather than cultural similarity.

Acknowledgments

This work was supported in part by the Air Force Office of Scientific Research under grant FA9550-22-1-0099. We thank members of the LAUNCH Lab for their helpful discussions, and the annotators who contributed to building MCLASH. We also thank Sai Krishna Gandra for his work on dataset quality checking.

References

Utkarsh Agarwal, Kumar Tanmay, Aditi Khandelwal, and Monojit Choudhury. Ethical reasoning and moral value alignment of llms depend on the language we prompt them in. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pp. 6330–6340, 2024.

Orevaoghene Ahia, Sachin Kumar, Hila Gonen, Jungo Kasai, David R Mortensen, Noah A Smith, and Yulia Tsvetkov. Do all languages cost the same? tokenization in the era of commercial language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 9904–9923, 2023.

Larry Alexander and Michael Moore. Deontological ethics. 2007.

Badr AlKhamissi, Muhammad ElNokrashy, Mai Alkhamissi, and Mona Diab. Investigating cultural alignment of large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 12404–12422, 2024.

Zhiyu An and Wan Du. Moralreason: Generalizable moral decision alignment for llm agents using reasoning-level reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pp. 37232–37239, 2026.

Naveen Arivazhagan, Ankur Bapna, Orhan Firat, Dmitry Lepikhin, Melvin Johnson, Maxim Krikun, Mia Xu Chen, Yuan Cao, George Foster, Colin Cherry, et al. Massively multilingual neural machine translation in the wild: Findings and challenges. *arXiv preprint arXiv:1907.05019*, 2019.

Elizabeth Ashford and Tim Mulgan. Contractualism. 2007.

Trevor Bench-Capon, Henry Prakken, and Giovanni Sartor. Argumentation in legal reasoning. In *Argumentation in artificial intelligence*, pp. 363–382. Springer, 2009.

Tarek R Besold and Sara L Uckelman. The what, the why, and the how of artificial explanations in automated decision-making. *arXiv preprint arXiv:1808.07074*, 2018.

Terra Blevins, Tomasz Limisiewicz, Suchin Gururangan, Margaret Li, Hila Gonen, Noah A Smith, and Luke Zettlemoyer. Breaking the curse of multilinguality with cross-lingual expert language models. In *Proceedings of the 2024 conference on empirical methods in natural language processing*, pp. 10822–10837, 2024.

David O Brink. Rawlsian constructivism in moral theory. *Canadian Journal of philosophy*, 17 (1):71–90, 1987.

Mohna Chakraborty, Lu Wang, and David Jurgens. Structured moral reasoning in language models: A value-grounded evaluation framework. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 30283–30311, 2025.

Yu Ying Chiu, Liwei Jiang, and Yejin Choi. Dailydilemmas: Revealing value preferences of llms with quandaries of daily life. *arXiv preprint arXiv:2410.02683*, 2024.

Yu Ying Chiu, Michael S Lee, Rachel Calcott, Brandon Handoko, Paul de Font-Reaulx, Paula Rodriguez, Chen Bo Calvin Zhang, Ziwen Han, Udari Madhushani Sehwag, Yash Maurya, et al. Morebench: Evaluating procedural and pluralistic moral reasoning in language models, more than outcomes. *arXiv preprint arXiv:2510.16380*, 2025.

William W Cobern. Constructivism. *Journal of Educational and Psychological Consultation*, 4 (1):105–112, 1993.

Jean Cohen. Discourse ethics and civil society. *Philosophy & social criticism*, 14(3-4):315–337, 1988.

Jules L Coleman and Brian Leiter. Legal positivism. *A companion to philosophy of law and legal theory*, pp. 228–248, 2010.

Ann Cudd and Seena Eftekhari. Contractarianism. 2000.

Jonathan Dancy. Moral particularism. 2001.

Jonathan Dancy. *Ethics without principles*. Clarendon Press, 2004.

Norman Daniels. Reflective equilibrium and archimedean points. *Canadian Journal of Philosophy*, 10(1):83–103, 1980.

Werner Delanoy. What is culture. *The Cambridge handbook of intercultural communication*, pp. 17–34, 2020.

Ezekiel J Emanuel. The beginning of the end of principlism–principles of biomedical ethics by tom l. beauchamp and james f. childress. *The Hastings Center Report*, 25(4):37, 1995.

Charles Ess. Ethical pluralism and global information ethics. *Ethics and Information Technology*, 8(4):215–226, 2006.

Sualeha Farid, Jayden Lin, Zean Chen, Shivani Kumar, and David Jurgens. One model, many morals: Uncovering cross-linguistic misalignments in computational moral reasoning. *arXiv preprint arXiv:2509.21443*, 2025.

Ruixiang Feng, Shen Gao, Xiuying Chen, Lisi Chen, and Shuo Shang. Culfit: A fine-grained cultural-aware llm training paradigm via multilingual critique data synthesis. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 22413–22430, 2025.

Alec Fisher. *The logic of real arguments*. Cambridge University Press, 2004.

Joseph F Fletcher. Situation ethics: The new morality. 1966.

R Edward Freeman. *Strategic management: A stakeholder approach*. Cambridge university press, 2010.

Leilani H Gilpin, David Bau, Ben Z Yuan, Ayesha Bajwa, Michael Specter, and Lalana Kagal. Explaining explanations: An overview of interpretability of machine learning. In *2018 IEEE 5th International Conference on data science and advanced analytics (DSAA)*, pp. 80–89. IEEE, 2018.

Hanjo Glock. What is analytic philosophy. *Journal for the History of Analytical Philosophy*, 2 (2), 2013.

Jesse Graham, Jonathan Haidt, Sena Koleva, Matt Motyl, Ravi Iyer, Sean P Wojcik, and Peter H Ditto. Moral foundations theory: The pragmatic validity of moral pluralism. In *Advances in experimental social psychology*, volume 47, pp. 55–130. Elsevier, 2013.

Hilary Greaves and Toby Ord. Moral uncertainty about population axiology. *J. Ethics & Soc. Phil.*, 12:135, 2017.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.

Jurgen Habermas. Between facts and norms: An author's reflections. *Denv. UL Rev.*, 76:937, 1998.

Jürgen Habermas. Discourse ethics. In *Ethics: Contemporary Readings*, pp. 146–153. Routledge, 2004.

Dan Hendrycks, Collin Burns, Steven Basart, Andrew Critch, Jerry Li, Dawn Song, and Jacob Steinhardt. Aligning ai with shared human values. In *International Conference on Learning Representations*.

Geert Hofstede and Michael H Bond. Hofstede's culture dimensions: An independent validation using rokeach's value survey. *Journal of cross-cultural psychology*, 15(4):417–433, 1984.

John Horton. Rawls, public reason and the limits of liberal justification. *Contemporary political theory*, 2(1):5–23, 2003.

Brian Hu, Bill Ray, Alice Leung, Amy Summerville, David Joy, Christopher Funk, and Arslan Basharat. Language models are alignable decision-makers: Dataset and application to the medical triage domain. In Yi Yang, Aida Davani, Avi Sil, and Anoop Kumar (eds.), *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 6: Industry Track)*, pp. 213–227, Mexico City, Mexico, June 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.naacl-industry.18. URL https://aclanthology.org/2024.naacl-industry.18/.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, et al. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*, 2024.

Rosalind Hursthouse. On virtue ethics. In *Applied ethics*, pp. 29–35. Routledge, 2017.

Jaedong Hwang, Kumar Tanmay, Seok-Jin Lee, Ayush Agrawal, Hamid Palangi, Kumar Ayush, Ila Fiete, and Paul Pu Liang. Learn globally, speak locally: Bridging the gaps in multilingual reasoning. *arXiv preprint arXiv:2507.05418*, 2025.

Zhijing Jin, Max Kleiman-Weiner, Giorgio Piatti, Sydney Levine, Jiarui Liu, Fernando Gonzalez Adauto, Francesco Ortu, András Strausz, Mrinmaya Sachan, Rada Mihalcea, et al. Language model alignment in multilingual trolley problems. In *The Thirteenth International Conference on Learning Representations*.

Zhijing Jin, Sydney Levine, Fernando Gonzalez Adauto, Ojasv Kamal, Maarten Sap, Mrinmaya Sachan, Rada Mihalcea, Joshua B Tenenbaum, and Bernhard Schölkopf. When to make exceptions: Exploring language models as accounts of human moral judgment. In *Advances in Neural Information Processing Systems*, 2022.

Philip H Jos. Social contract theory: Implications for professional ethics. *The American Review of Public Administration*, 36(2):139–155, 2006.

Christine Koggel and Joan Orme. Care ethics: New theories and applications, 2010.

Shivani Kumar and David Jurgens. Are rules meant to be broken? understanding multilingual moral reasoning as a computational pipeline with unimoral. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 5890–5912, 2025.

Hugh LaFollette. Pragmatic ethics. 1999.

Ayoung Lee, Ryan Sungmo Kwon, Peter Railton, and Lu Wang. Clash: Evaluating language models on judging high-stakes dilemmas from multiple perspectives. *arXiv preprint arXiv:2504.10823*, 2025.

Cheng Li, Mengzhuo Chen, Jindong Wang, Sunayana Sitaram, and Xing Xie. Culturellm: Incorporating cultural differences into large language models. *Advances in Neural Information Processing Systems*, 37:84799–84838, 2024a.

Cheng Li, Damien Teney, Linyi Yang, Qingsong Wen, Xing Xie, and Jindong Wang. Culturepark: Boosting cross-cultural understanding in large language models. *Advances in Neural Information Processing Systems*, 37:65183–65216, 2024b.

Cristal Lopez, Mariana Vazquez, and Anita Sohn McCormick. Familismo, respeto, and bien educado: Traditional/cultural models and values in latinos. In *Family literacy practices in Asian and Latinx families: Educational and cultural considerations*, pp. 87–102. Springer, 2022.

Michael MacAskill, Krister Bykvist, and Toby Ord. *Moral uncertainty*. Oxford University Press, 2020.

John Macquarrie. Existentialism. 1972.

Arijit Maji, Raghvendra Kumar, Akash Ghosh, Nemil Shah, Abhilekh Borah, Vanshika Shah, Nishant Mishra, Sriparna Saha, et al. Drishtikon: A multimodal multilingual benchmark for testing language models' understanding on indian culture. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 1289–1313, 2025.

John Stuart Mill. Utilitarianism. In *Seven masterpieces of philosophy*, pp. 329–375. Routledge, 2016.

Albert W Musschenga. Empirical ethics, context-sensitivity, and contextualism. *Journal of medicine and philosophy*, 30(5):467–490, 2005.

Junho Myung, Nayeon Lee, Yi Zhou, Jiho Jin, Rifki A Putri, Dimosthenis Antypas, Hsuvas Borkakoty, Eunsu Kim, Carla Perez-Almendros, Abinew A Ayele, et al. Blend: A benchmark for llms on everyday knowledge in diverse cultures and languages. *Advances in Neural Information Processing Systems*, 37:78104–78146, 2024.

Tarek Naous, Michael J Ryan, Alan Ritter, and Wei Xu. Having beer after prayer? measuring cultural bias in large language models. In *Proceedings of the 62nd annual meeting of the association for computational linguistics (volume 1: Long papers)*, pp. 16366–16393, 2024.

Peter Newmark. *A textbook of translation*, volume 66. Prentice hall New York, 1988.

Ha-Thanh Nguyen. A brief report on lawgpt 1.0: A virtual legal assistant based on gpt-3. *arXiv preprint arXiv:2302.05729*, 2023.

Allen Nie, Yuhui Zhang, Atharva Shailesh Amdekar, Chris Piech, Tatsunori B Hashimoto, and Tobias Gerstenberg. Moca: Measuring human-language model alignment on causal and moral judgment tasks. *Advances in Neural Information Processing Systems*, 36:78360–78393, 2023.

Shota Onohara, Atsuyuki Miyai, Yuki Imajuku, Kazuki Egashira, Jeonghun Baek, Xiang Yue, Graham Neubig, and Kiyoharu Aizawa. Jmmmu: A japanese massive multi-discipline multimodal understanding benchmark for culture-aware evaluation. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 932–950, 2025.

Martin Peterson. *An introduction to decision theory*. Cambridge University Press, 2017.

David Phillips. *Rossian ethics: WD Ross and contemporary moral theory*. Oxford University Press, 2019.

Giada Pistilli, Alina Leidinger, Yacine Jernite, Atoosa Kasirzadeh, Alexandra Sasha Luccioni, and Margaret Mitchell. Civics: Building a dataset for examining culturally-informed values in large language models. In *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, volume 7, pp. 1132–1144, 2024.

Peter Railton. Moral realism. *The philosophical review*, 95(2):163–207, 1986.

David Daiches Raphael. *The impartial spectator: Adam Smith's moral philosophy*. Clarendon Press, 2007.

Joseph Raz. Right-based moralities. In *Rights and Reason: Essays in Honor of Carl Wellman*, pp. 177–196. Springer, 1984.

Christian Reus-Smit et al. Constructivism. *Theories of international relations*, 3:188–212, 2005.

Milton Rokeach. Rokeach value survey. *The nature of human values.*, 1967.

Keenan Samway, Max Kleiman-Weiner, David Guzman Piedrahita, Rada Mihalcea, Bernhard Schölkopf, and Zhijing Jin. Are language models consequentialist or deontological moral reasoners? In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 30687–30714, 2025.

Nino Scherrer, Claudia Shi, Amir Feder, and David Blei. Evaluating the moral beliefs encoded in llms. *Advances in Neural Information Processing Systems*, 36, 2024.

Shalom H Schwartz. An overview of the schwartz theory of basic values. *Online readings in Psychology and Culture*, 2(1), 2012.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Shuaijie She, Wei Zou, Shujian Huang, Wenhao Zhu, Xiang Liu, Xiang Geng, and Jiajun Chen. Mapo: Advancing multilingual reasoning through multilingual-alignment-as-preference optimization. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 10015–10027, 2024.

Abhishek Sheetal, Shilpa Madan, Rui Ling Lee, and Krishna Savani. What values best distinguish the world's cultures? the machine learning-based cultural values inventory. *PNAS nexus*, 4(8):pgaf229, 2025.

Karan Singhal, Shekoofeh Azizi, Tao Tu, S Sara Mahdavi, Jason Wei, Hyung Won Chung, Nathan Scales, Ajay Tanwani, Heather Cole-Lewis, Stephen Pfohl, et al. Large language models encode clinical knowledge. *Nature*, 620(7972):172–180, 2023.

Zhi Rui Tam, Cheng-Kuang Wu, Yu Ying Chiu, Chieh-Yen Lin, Yun-Nung Chen, and Hung-yi Lee. Language matters: How do multilingual input and reasoning paths affect large reasoning models? *arXiv preprint arXiv:2505.17407*, 2025.

Elizaveta Tennant, Stephen Hailes, and Mirco Musolesi. Moral alignment for llm agents. In *International Conference on Learning Representations*, volume 2025, pp. 97477–97510, 2025.

George Tovstiga. *Strategy Praxis: Insight-Driven, First Principles-Based Strategic Thinking, Analysis, and Decision-Making*. Springer, 2023.

Michael Walzer. The communitarian critique of liberalism. *Political theory*, 18(1):6–23, 1990.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.

Allen W Wood. *Kantian ethics*, volume 60. Cambridge University Press Cambridge, 2008.

Weidong Wu, Qinlin Zhao, Hao Chen, Lexin Zhou, Defu Lian, and Hong Xie. Exploring the choice behavior of large language models. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 5194–5214, 2025a.

Ya Wu, Qiang Sheng, Danding Wang, Guang Yang, Yifan Sun, Zhengjia Wang, Yuyan Bu, and Juan Cao. The staircase of ethics: Probing llm value priorities through multi-step induction to complex moral dilemmas. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 15961–15981, 2025b.

WVS. Wvs cultural map: 2023 version released, 2023-02-17. URL https://www.worldvaluessurvey.org/WVSNewsShow.jsp?ID=467. Accessed: 2025-03-01.

Chaojun Xiao, Xueyu Hu, Zhiyuan Liu, Cunchao Tu, and Maosong Sun. Lawformer: A pre-trained language model for chinese legal long documents. *AI Open*, 2:79–84, 2021.

Shaoyang Xu, Yongqi Leng, Linhao Yu, and Deyi Xiong. Self-pluralising culture alignment for large language models. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 6859–6877, 2025.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

Dongkeun Yoon, Joel Jang, Sungdong Kim, Seungone Kim, Sheikh Shafayat, and Minjoon Seo. Langbridge: Multilingual reasoning without multilingual supervision. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7502–7522, 2024.

Morris Zelditch. Theories of legitimacy. *The psychology of legitimacy: Emerging perspectives on ideology, justice, and intergroup relations*, 33, 2001.

Hengyuan Zhang, Chenming Shang, Sizhe Wang, Dongdong Zhang, Yiyao Yu, Feng Yao, Renliang Sun, Yujiu Yang, and Furu Wei. Shifcon: Enhancing non-dominant language capabilities with a shift-based multilingual contrastive framework. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 4818–4841, 2025.

Weixiang Zhao, Jiahe Guo, Yang Deng, Tongtong Wu, Wenxuan Zhang, Yulin Hu, Xingyu Sui, Yanyan Zhao, Wanxiang Che, Bing Qin, et al. When less language is more: Language-reasoning disentanglement makes llms better multilingual reasoners. *arXiv preprint arXiv:2505.15257*, 2025.

Huichi Zhou, Zehao Xu, Munan Zhao, Kaihong Li, Yiqiang Li, and Hongtao Wang. Moral reasoning across languages: The critical role of low-resource languages in llms. *arXiv preprint arXiv:2504.19759*, 2025.

Wenhao Zhu, Shujian Huang, Fei Yuan, Shuaijie She, Jiajun Chen, and Alexandra Birch. Question translation training for better multilingual reasoning. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 8411–8423, 2024.

A MCLASH Curation

A.1 Selection of the model for adaptation

We compared two models, Qwen3-32B and GPT-4o (Hurst et al., 2024), evaluating their performance in adapting culturally specific items (Newmark, 1988) (Figure 7). Qwen3-32B demonstrated stronger adaptation abilities, whereas GPT-4o mainly produced direct translations with limited cultural considerations. Based on these results, we selected Qwen3-32B for adapting CLASH multilingually, and subsequently asked human annotators to review and refine the outputs as needed.

A.2 Details of Adaptation

The prompts used for adaptation, along with the checklist for human inspectors, are presented in Figures 8 through 12. We first adapt situations from CLASH using the prompt in Figure 8. These adapted situations are then presented to human inspectors, who evaluate and revise them using the checklist in Figure 10 and 11. After finalizing the situations, we use them to adapt the character descriptions with the prompt in Figure 9. For the character descriptions, we found that Qwen3-32B already performs well in adaptation, with only minor language issues, such as occasionally generating text in languages irrelevant to the



Figure 7: **Figure for model selection**

target language. Therefore, we corrected these minor issues manually to ensure linguistic quality, without applying an extensive checklist as was done for the situations.

Because adaptation revises entities rather than assigning labels, multiple revision choices may be equally appropriate for a culture. For example, the U.S. tech company Meta maps to any large Korean tech company such as Naver or Kakao. With many valid answers, a single numeric inter-annotator agreement is not well-defined. We instead ensure the quality with a rigorous inspection checklist and a second pass in which the authors back-translate each adapted narrative into English to flag misadapted or unadapted entities, such as a company name that is still American. We then discussed the flagged cases with the annotators.

A.3 Dataset Statistics

In this section, we present descriptive statistics for the MCLASH dataset. Table 4 reports the total number of situations and the average number of tokens for the Situation, Action, and Character Descriptions for each language. Following the cultural adaptation stages described in Section 3, we discard datapoints that contain situations that were irrelevant to the culture or inadequately adapted by the model during the data curation pipeline.

Our results exhibit a consistent trend in which culturally adapted variants yield a higher average number of tokens compared to English, with increases of up to six times in some cases. This observation aligns with prior work showing that equivalent content across different languages may differ in token count by up to 5× compared to that of English due to linguistic and tokenization factors (Ahia et al., 2023).

B Method

B.1 Details of Grounds and Prompts

We present the six dimensions and their corresponding grounds below, with specific prompts for selecting the grounds and their descriptions presented in Figures 14 and 15. We also provide the instructions used to generate responses based on the selected grounds in Figure 16.

Your job is to translate/adapt an existing English data to {lan} culture. The data consists of these elements: Situation, Action, and Reasons.

Situation: A dilemma situation.
Action: The hard-to-decide action involved in the situation.
Reasons: Consists of 'Supporting Reason' and 'Opposing Reason'. 'Supporting Reason' is the reason supporting the action, 'Opposing Reason' is the reason opposing the action.

Checklist:

- You should keep the response in {lan}
- You should change all the named entities into something relevant to {lan} culture.
- Try not to use a widely recognized name, but rather use a generic name that is likely to be used in {lan} culture. If it is inevitable to use an entity name that is a widely recognized name in the culture, you should make the narrative factual. For example, if you want to use the name Faker, who is a famous pro-gamer in South Korea, you cannot include false information like: "Faker is a famous singer in South Korea".
- If some parts of the narratives (e.g. historical events that only occurred in U.S.) are unlikely to appear in {lan} culture, you should modify the content a bit to make it culturally adapted to {lan} culture.
- However, make sure that the human values involved in making decisions in the situation are preserved.
- Try not to omit details in the original dilemma situation when trying to adapt it to {lan} culture. You often tend to make the content shorter by summarizing, but you should try not to do that in this task. Each sentence in the original situation should have a corresponding sentence in the adapted situation, unless the sentence is totally not adaptable in {lan} culture.
- Be extra careful of the wording of the supporting/opposing reasons. The wording of the adapted reasons matters. Substitute the reasons in this phrase – "believing that {{reason}} is important" – and see if it makes sense. This phrase is written in English, but this principle should be applied when writing the reasons in the target language {lan}. Make sure that the reasons are phrases, not sentences.
- Do not try to translate the original content and then add some culturally adapted paragraphs. For example, do not try to organize your response like: In America, these events happened, but if we adapt this in {lan} context, ... You should directly adapt the context, and should not mention in your response that you are trying to adapt an original context to a {lan} context.

The input would be provided in the following format:

Input:
Situation: {{situation}}
Action: {{action}}
Supporting Reason: {{supporting reason}}
Opposing Reason: {{opposing reason}}

You should output the adapted situation, action and reasons in the following format. Strictly adhere to the output format since it would be automatically parsed.
However, be careful not to output {{adapted situation}}, {{adapted action}}, {{adapted supporting reason}}, or {{adapted opposing reason}} in your response directly; these are just placeholders. You should output the adapted contents directly.

Your answer:
Situation: {{adapted situation}}
Action: {{adapted action}}
Supporting Reason: {{adapted supporting reason}}
Opposing Reason: {{adapted opposing reason}}

Figure 8: **Prompt used for culturally adapting the situation, action, and reasons**

Your job is to translate/adapt an existing English character description to {lan} culture. The original English character description is made by intertwining the original supporting reason and opposing reason in a specific way.

These are the explanations for the categories of the character description:

- Straightforward: one reason is clearly prioritized over the other
- Simple Contrast: the character equally endorses both reasons
- Swayed Contrast: the character acknowledges both reasons but prioritizes one

You should translate/adapt the character description to lan culture while preserving the original meaning and structure of the character description.
I will also provide the adapted supporting reason and opposing reason, which are the reasons that the adapted character description should be based on.
Do not leave out details in the original character description. This means that you should not summarize the content; you should include the rich details presented in the original character description.

Checklist:

- The original character's name is always "Character A", but you should adapt this into a culturally appropriate name in {lan}. Remember that you should not directly translate "Character A", but adapt it into a name that is likely to be used in {lan} culture. Also, use the same name for "Character A" for all of the descriptions for consistency. Make sure to change all references to "Character A" in the character descriptions (e.g. "A was", "A is", "Character A decided to", ...) to the adapted name.
- The adapted name should be strictly in {lan} language.
- The original character descriptions are based on the supporting and opposing reasons. Since these reasons are culturally adapted, the character descriptions should also be modified to reflect the adapted reasons. Apart from the "reasons" aspect, the original and the translated/adapted narratives should be equivalent in meaning, and you should not leave out details from the original character description while translating/adapting.

The input would be provided in the following format:

Input:
Original Supporting Reason: {{supporting reason}}
Original Opposing Reason: {{opposing reason}}
Straightforward Character Description - 1: {{straight char description 1}}
Straightforward Character Description - 2: {{straight char description 2}}
Simple Contrast Character Description: {{simple contrast char description}}
Swayed Contrast Character Description - 1: {{swayed contrast char description 1}}
Swayed Contrast Character Description - 2: {{swayed contrast char description 2}}
Adapted Supporting Reason: {{adapted supporting reason}}
Adapted Opposing Reason: {{adapted opposing reason}}

You should output the adapted character descriptions in the following format. Strictly adhere to the output format since it would be automatically parsed.

Your answer:
Name of Character A: {{adapted character name}}
Straightforward Character Description - 1: {{adapted straight char description 1}}
Straightforward Character Description - 2: {{adapted straight char description 2}}
Simple Contrast Character Description: {{adapted simple contrast char description}}
Swayed Contrast Character Description - 1: {{adapted swayed contrast char description 1}}
Swayed Contrast Character Description - 2: {{adapted swayed contrast char description 2}}

Figure 9: **Prompt used for culturally adapting the character descriptions**

Please inspect the large language model (LLM)-generated situation, action, and reasons and modify it accordingly based on the checklist below:

- Grammatical Correctness: Please correct the grammar if necessary.
- Check the reasons (supporting reason vs opposing reason) and see if they make sense in the context of your culture. Then, examine the situation and action to determine whether it aligns with those reasons and whether the content is culturally appropriate and reasonable.
- If the narrative has too many problems and is too hard to modify, you can request to regenerate the translation. Indicate it as "redo".

Figure 10: **General guidelines for annotating situation, action, and reasons**

Dataset	Language	# Situations	Avg # Tokens		
			Situation	Action	Char Desc
CLASH (en)	English	345	659.14	7.34	87.84
$\text{MCLASH}_{\text{es}}$	Spanish	319	787.30	11.98	141.52
$\text{MCLASH}_{\text{hi}}$	Hindi	277	2826.07	39.77	535.47
$\text{MCLASH}_{\text{kr}}$	Korean	317	1141.53	18.80	281.78
$\text{MCLASH}_{\text{ms}}$	Malay	330	991.70	13.37	184.82
$\text{MCLASH}_{\text{zh-CN}}$	Chinese	264	811.36	14.80	256.19
MCLASH	6 languages	1852	1168.14	17.08	238.54

Table 4: **MCLASH dataset statistics**

- **Normative Authority**: Truth-based Authority (Railton, 1986), Reason-Based Authority (Wood, 2008; Reus-Smit et al., 2005), Agreement-Based Authority (Jos, 2006; Brink, 1987; Ashford & Mulgan, 2007), Institution-Based Authority (Zelditch, 2001; Coleman & Leiter, 2010; Walzer, 1990), Responsibility-Based Authority (Macquarrie, 1972), Relation-Based Authority (Cobern, 1993; Cohen, 1988), Human-Nature-Based Authority.
- **Value Systems**: Moral Foundations Theory (Graham et al., 2013), Schwartz's Value System (Schwartz, 2012), Hofstede's Cultural Dimensions (Hofstede & Bond, 1984), Rokeach's Value Survey (Rokeach, 1967)
- **Ethical Theories**: Deontology (Alexander & Moore, 2007), Utilitarianism (Mill, 2016), Virtue Ethics (Hursthouse, 2017), Care Ethics (Koggel & Orme, 2010), Right-based Ethics (Raz, 1984), Contractarianism (Cudd & Eftekhari, 2000), Ethical Pluralism (Ess, 2006), Pragmatic Ethics (LaFollette, 1999)
- **Cognitive Reasoning Strategies**: Step-by-step reasoning (Wei et al., 2022), Harm-benefit analysis, Stakeholder analysis (Freeman, 2010), Counterfactual reasoning (Fisher, 2004), Consequentialist framing (Hendrycks et al.), First-principles reasoning (Tovstiga, 2023)
- **Conflict Handling Strategies**: Context-sensitive resolution (Dancy, 2001; Musschenga, 2005), Principle-based resolution (Emanuel, 1995; Phillips, 2019), Coherence-based resolution (Daniels, 1980), Adversarial Testing (Bench-Capon et al., 2009), Perspective-based Resolution, Spectator-based Resolution (Raphael, 2007), Procedural Resolution (Habermas, 2004; 1998; Horton, 2003)
- **Moral Uncertainty**: Monistic Commitment (Railton, 1986), Multi-framework Consideration (Ess, 2006), Probablistic Moral Uncertainty (MacAskill et al., 2020; Greaves & Ord, 2017), Optimization (Peterson, 2017), Maximin Reasoning (Peterson, 2017)

Situation:

- **Narrative Quality**: Please modify the narrative accordingly to ensure coherence, consistency, meaning, and naturalness. If the content is unnecessary and hard to modify, feel free to delete the content.
  - **Coherence**: Check whether the narrative is logically correct and makes sense
  - **Consistency**: The narrative should consistently stay on the same topic or theme.
  - **Meaning**: If a part is not culturally adapted, the meaning should be equivalent.
  - **Naturalness**: Check whether the language sounds natural and fluent to native speakers
- **Cultural Adaptation**: Please revise any entities that are not culturally appropriate or well-adapted. Don't worry about identifying every single entity; just use your best judgment. As long as you feel there is need, feel free to make edits to make the narrative as natural as possible to a given culture. This framework is meant to guide you, especially when you're unsure.
  - **Context-level Adaptation**
    - Does this situation have a chance to occur in your culture?
    - Do the specific parts (e.g. events, explanations for specific phenomenon, character behaviors) in the narrative all make sense in your culture?
  - **Entity-level Adaptation**: You should focus on the following entities and evaluate whether they are well-adapted to the specific culture (We follow *Newmark's CSI classification framework* (Newmark, 1988))
    - **Ecology**: geographic features that are often unique to a specific place, such as animals, plants, local winds, mountains, plains, ice, etc.
    - **Material Culture**: artefacts, or physical items made or used by a particular culture, such as food, clothes, houses and towns, and transport, etc.
    - **Social Culture**: work or leisure activities, including sports and media entertainment
    - **Institutions, Organizations, Names, and Ideas**: such as political, social, religious, social, artistic, administrative concepts, ideas, institution names, names of people, etc.
    - **Gestures and Habits**: such as body language, greetings
  - **Idioms, Proverbs, Symbols, Figure of Speech**
  - **Unit and format**: unit of measurement, currency, number format
- **Factuality**:
  - If well-recognized real names of institutions, people, organizations, etc. are used, the narrative using the names should be factual.
  - If the name is fictional or not well-recognized, there's no need to verify the factuality of the narrative.

Action:

- Check whether the action is relevant to the adapted situation, and modify accordingly.

Reasons:

- Same as the action checklist item; you should check whether the reasons are relevant to the adapted situation, and modify accordingly.
- The reason should be equivalent to the original reason except for the culturally adapted part. The supporting reason should still be the reason to support the action, and the opposing reason should still be the reason to oppose the action.
- Format of the Reasons:
  - The reasons should be a phrase, not a sentence.
  - Substitute the adapted reason into this phrase - "believing that reason is important" - and make sure it makes sense. This phrase is written in english but you should translate it in your own language and use it.

Figure 11: **Task-specific checklist for annotating situation, action, and reasons**

Situation:

- **Narrative Quality**:
  - **Coherence**: e.g.) A non-coherent example would be: "To decrease racism, the country decided not to produce any juice".
  - **Consistency**: e.g.) Suppose the original narrative focuses on racism. During the translation/cultural adaptation process, the narrative might be changed to focus on discrimination of ethnic minorities. If so, the narrative should always adhere to the topic (ethnic minorities), and not deviate from this topic, such as talking about racism briefly.
  - **Meaning**: e.g.) Suppose that in the original content: "Jane proposed a moral reasoning dataset in response to public concerns." Then the translation should NOT be "A moral reasoning dataset is rejected by Jane due to public concerns", or "The public criticized Jane for not proposing a moral reasoning dataset" (distortion of meaning).
  - **Naturalness**
- **Cultural Adaptation**:
  - **Context-level Adaptation**
  - **Entity-level Adaptation**:
    - **Ecology**: e.g.) sage branches, Vail, Alps, Grand Canyon, San Diego Zoo, Capuchin, etc.
    - **Material Culture**: e.g.) meatball sub, MonkeyShine Beer poster, hamburger, Soap Opera Digest, specific design of housing, type of vehicle owned or used, typical personal possessions
    - **Social Culture**: e.g.) Another World (TV series), Thanksgiving, Days of Our Lives (Drama), bridesmaids, Halloween, etc.
    - **Institutions, Organizations, Names, and Ideas**: e.g.) Alan Alda, Mattress King, Wendy's, FICA, Fortunata Fashions, etc.
    - **Gestures and Habits**: e.g.) giving a thumbs up, nodding or shaking heads, "honk honk", "Cha-ching", etc.
  - **Idioms, Proverbs, Symbols, Figure of Speech**
  - **Unit and format**: e.g.) Fahrenheit vs Celsius, $ vs €, y/m/d vs m/d/y
- **Factuality**: e.g.) If a narrative mentions a real-world figure such as "Trump" (Donald Trump), ensure that no incorrect factual claims are introduced (e.g., "Trump is in the Democratic Party").

Action:

- e.g.) Suppose the original situation discusses "racism between black and white", and the action was "Implementing an alert system to detect racism against Black people". Then, a culturally adapted situation may be about "discrimination of ethnic minorities", and the action should also correspond to the following situation, and could potentially be "Implementing an alert system for discrimination against ethnic minorities".

Figure 12: **Examples of task-specific checklist items from Figure 11**: We present these examples to help human inspectors better understand the checklist items.



Figure 13: **Dimensions, grounds, and descriptions**: We present six dimensions, each with a set of specific grounds and descriptions that the target model can select from.

B.2 Prompts Used for Generating the Training Dataset

The prompt used for extracting values from the WVS questionaire is presented in Figure 17.

C Results

C.1 Full Results and Comparison with MoReBench Dimensions

The full per-language results for MCLASH, MMoralExceptQA, and MoCa are presented in Table 5 (Qwen3-4B), Table 6 (Qwen3-8B), and Table 7 (Gemma3-4B). For Qwen3-4B, Table 5 additionally includes two settings: MoRe, a baseline that replaces our theoretical grounds with the MoReBench dimensions,[3] and MET-D(s), a variant trained on situation-only data that samples reasoning chains in the same 1:1:1 (yes/no/ambiguous) label ratio as MET-D but, lacking character descriptions, has no verifiable ground truth for rejection sampling. Table 5 shows that MET outperforms MoRe and MET-D outperforms MET-D(s), further validating our approach.

C.2 Full Numbers for the Native Language Reasoning Experiment

The full numbers for comparing 1) base model (Qwen3-4B) with no language enforcement on reasoning chains, 2) base model with explicit prefill tokens to enforce native-language reasoning, 3) our trained model plus prompting without enforcement, and 4) our full method, MET-D, with training, prompting, and enforcement are presented in Table 8.

C.3 Comparison of the Ability of *Theory-Guided Reasoning* of the Base Model versus the Trained Model

Figure 18 presents examples of the *Theory-Guided Reasoning* output for the base and trained models.

[3]Since MoReBench is strictly English, we translate the criteria and descriptions using Google Translate for each target language, and apply the same *ground selection* process.

I will provide you with a situation, and suppose you should make a decision. You should select a rubric (set of criteria) that the reasoning process for making the decision should follow. You should only output the criteria. Here are all dimensions, the names of the criteria, and their descriptions. You can select multiple criteria from the same dimension or not select any.

Normative Authority

- **Truth-based Authority:** Ground your reasoning in the assumption that there are objective moral principles or values. Justify your conclusion by appealing to principles that would be true independently of cultural agreement or personal preference.
- **Reason-Based Authority:** Ground your reasoning in principles or values that any rational agent would be committed to. Emphasize logical consistency, universalizability, and coherence.
- **Agreement-Based Authority:** Justify the moral conclusion by appealing to what free and equal agents would agree to under fair conditions. Emphasize reciprocity, fairness, and justifiability to all affected parties.
- **Institution-Based Authority:** Justify the decision by appealing to established social roles, rules, laws, values, or norms that are taken to be legitimate. Emphasize stability, institutional legitimacy, and shared standards.
- **Responsibility-Based Authority:** Justify the conclusion in terms of authentic choice and responsibility for the decision.
- **Relation-Based Authority:** Justify the conclusion in terms of shared commitments and endorsed values. Emphasize collective endorsement rather than objective truth.
- **Human-Nature-Based Authority:** Ground your reasoning in features of human psychology, emotional structure, or human flourishing. Explain why the moral conclusion aligns with how humans are, or could be, constituted.

Value Systems

- **Moral Foundations Theory:** Identify which moral foundations are most relevant in this case (e.g., care/harm, fairness/cheating, loyalty/betrayal, authority/subversion, sanctity/degradation, liberty/oppression). Frame your reasoning around the protection or violation of these foundations.
- **Schwartz's Value System:** Identify which core human values (e.g., benevolence, universalism, security, conformity, achievement, power, tradition, self-direction) are most implicated in this situation. Explain how the conflict reflects tension between these values.
- **Hofstede's Cultural Dimensions:** Analyze the situation through relevant cultural dimensions (e.g., individualism vs collectivism, power distance, uncertainty avoidance, masculinity vs femininity, long-term orientation). Explain how different cultural orientations would interpret the issue.
- **Rokeach's Value Survey:** Distinguish between terminal values (desired end states, such as freedom or equality) and instrumental values (modes of conduct, such as honesty or responsibility). Identify which values are in tension and how they shape the moral issue.

Ethical Theories

- **Deontology:** Evaluate the action based on whether it conforms to moral duties. Determine whether the principle behind the action could be consistently universalized.
- **Utilitarianism:** Evaluate the action by comparing its overall consequences. Determine which option maximizes overall well-being and minimizes harm.
- **Virtue Ethics:** Evaluate the action in terms of character and moral excellence. Consider what a virtuous person would do in this situation and why.
- **Care Ethics:** Evaluate the situation by focusing on relationships, dependency, and responsibility. Consider how care, empathy, and responsiveness should guide the decision.
- **Right-based Ethics:** Determine whether the action respects or violates fundamental rights. Give priority to protecting individual entitlements and dignity.
- **Contractarianism:** Evaluate the action based on whether it could be justified to all affected parties under fair conditions of agreement.
- **Ethical Pluralism:** Evaluate the issue using multiple ethical frameworks and compare their relative importance without reducing them to a single rule.
- **Pragmatic Ethics:** Focus on the practical consequences of adopting this moral stance in real-world contexts. Consider adaptability, problem-solving, and long-term social functioning.

Figure 14: **Prompt for selecting the grounds**: We translate this prompt into the target languages using Google Translate to produce multilingual global set of grounds.

Cognitive Reasoning Strategies

- **Step-by-step reasoning:** Break down the moral issue into clearly sequenced steps. Make each assumption and inference explicit before reaching a conclusion.
- **Harm-benefit analysis:** Identify all foreseeable harms and benefits and use them in the analysis.
- **Stakeholder analysis:** Identify all affected stakeholders. Analyze how each party's rights, interests, risks, and perspectives are impacted.
- **Counterfactual reasoning:** Consider how the moral evaluation would change if key facts or minor details were different. Test the robustness of the conclusion under alternative scenarios.
- **Consequentialist framing:** Frame the issue primarily in terms of outcomes and systemic effects.
- **First-principles reasoning:** Begin from foundational moral assumptions and derive the conclusion through structured logical reasoning.

Conflict Handling Strategies

- **Context-sensitive resolution:** Resolve the conflict by carefully analyzing the specific relevant features of the case. Do not assume that general principles automatically override contextual factors.
- **Principle-based resolution:** Identify the relevant principles and determine how they rank or interact. Resolve the conflict by applying a structured hierarchy or balancing process.
- **Coherence-based resolution:** Revise principles and case judgments iteratively until they form a consistent and coherent moral position.
- **Adversarial Testing:** First construct the strongest arguments for each side. Then evaluate which position withstands critical scrutiny.
- **Perspective-based Resolution:** Evaluate the conflict from the standpoint of each affected party before reaching a conclusion.
- **Spectator-based Resolution:** Evaluate the conflict from the perspective of a spectator who is not directly involved in the situation.
- **Procedural Resolution:** When principles conflict, determine what decision procedure would be considered fair and legitimate by all affected parties.

Moral Uncertainty

- **Monistic Commitment:** Select the moral framework judged most defensible and reason exclusively within it.
- **Multi-framework Consideration:** Evaluate the issue from multiple moral frameworks and compare their conclusions without reducing them to a single metric.
- **Probabilistic Moral Uncertainty:** Assign relative credibility to competing moral theories and choose the most probable answer.
- **Optimization:** Calculate in terms of expected value, and select an action that maximizes the expected value.
- **Maximin Reasoning:** Choose the action or principle that leads to the least harmful outcome.

The output must strictly follow this format:
List the selected criteria one per line, including the name of the criterion.
You should output the name of the criteria in the exact same format as presented above.

An example output would be:
Normative Authority
- Reason-Based Authority: Ground your reasoning in principles or values that any rational agent would be committed to. Emphasize logical consistency, universalizability, and coherence.
- Agreement-Based Authority: ...
...
Value Systems
- Moral Foundations Theory: ...
...
... more dimensions and criteria
Situation:
{situation}

Figure 15: **Prompt for selecting the grounds, continued from Figure 14**

(a) MMoralExceptQA (macro F1 per language)

Method	en	es	hi	zh	avg
Base	67.26	65.62	55.17	63.83	62.97
MoRe	70.05	69.64	52.80	62.54	63.76
Δ	+2.79	+4.02	−2.37	−1.29	+0.79
MET	**73.08**	**73.01**	54.26	67.97	67.08
Δ	+5.82	+7.39	−0.91	+4.14	+4.11
MET-D	72.98	71.69	**59.46**	**68.42**	**68.14**
Δ	+5.72	+6.07	+4.29	+4.59	+5.17
MET-D (s)	71.98	72.60	58.69	64.37	66.91
Δ	+4.72	+6.98	+3.52	+0.54	+3.94

(b) MCLASH (clr / amb / F1 per language)

	en			es			hi		
Method	clr	amb	F1	clr	amb	F1	clr	amb	F1
Base	83.99	44.06	70.73	73.84	45.28	64.05	52.33	33.09	45.66
MoRe	83.84	44.93	70.94	72.98	37.74	61.19	50.71	30.07	43.38
Δ	−0.15	+0.87	+0.21	−0.86	−7.54	−2.86	−1.62	−3.02	−2.28
MET	85.51	41.45	70.97	73.26	45.14	63.70	**59.26**	23.68	47.10
Δ	+1.52	−2.61	+0.24	−0.58	−0.14	−0.35	+6.93	−9.41	+1.44
MET-D	**86.80**	**46.80**	**73.75**	73.70	**55.38**	**67.00**	57.94	**36.13**	**50.45**
Δ	+2.81	+2.74	+3.02	−0.14	+10.10	+2.95	+5.61	+3.04	+4.79
MET-D (s)	86.79	36.36	70.09	**74.92**	42.23	63.91	51.31	29.84	43.61
Δ	+2.80	−7.70	−0.64	+1.08	−3.05	−0.14	−1.02	−3.25	−2.05

	ko			ms			zh			
Method	clr	amb	F1	clr	amb	F1	clr	amb	F1	**avg**
Base	56.51	47.74	51.24	**77.57**	35.35	63.42	89.55	6.44	57.74	58.81
MoRe	57.80	46.30	51.74	74.40	35.95	61.54	**91.54**	3.03	56.68	57.58
Δ	+1.29	−1.44	+0.50	−3.17	+0.60	−1.88	+1.99	−3.41	−1.06	−1.23
MET	53.68	**52.23**	50.38	74.04	35.35	61.13	91.38	7.20	59.21	58.75
Δ	−2.83	+4.49	−0.86	−3.53	+0.00	−2.29	+1.83	+0.76	+1.47	−0.06
MET-D	63.55	50.16	**57.88**	76.63	**43.12**	**65.45**	91.47	**12.12**	**62.26**	**62.80**
Δ	+7.04	+2.42	+6.64	−0.94	+7.77	+2.03	+1.92	+5.68	+4.52	+3.99
MET-D (s)	**65.32**	43.67	57.52	77.55	25.00	59.67	88.68	7.95	58.07	58.81
Δ	+8.81	−4.07	+6.28	−0.02	−10.35	−3.75	−0.87	+1.51	+0.33	+0.00

(c) MoCa

Method	Clr	Amb	F1
Base	**45.88**	45.43	44.07
MoRe	32.80	46.57	37.37
Δ	−13.08	+1.14	−6.70
MET	40.55	43.67	42.43
Δ	−5.33	−1.76	−1.64
MET-D	36.73	**56.87**	**47.60**
Δ	−9.15	+11.44	+3.53
MET-D (s)	44.67	41.40	45.17
Δ	−1.21	−4.03	+1.10

Table 5: **Full per-language results (Qwen3-4B)**. For MMoralExceptQA, we report macro F1-score per language (zh, en, hi, es). For MCLASH, we report clear-cut accuracy (*clr*), ambiguous accuracy (*amb*), and macro F1 (*F1*) per language (en, es, hi, ko, ms, zh), with the average F1 across languages in the last column. For MoCa, we report accuracy on clear-cut (**Clr**) and ambiguous (**Amb**) instances alongside overall F1. **Bold** indicates the best result per column; underline indicates the second best. Δ rows show the difference from Base.

(a) MMoralExceptQA (macro F1 per language)

Method	en	es	hi	zh	avg
Base	67.87	65.62	53.35	58.82	61.42
MET	65.47	63.03	54.56	57.97	60.26
Δ	−2.40	−2.59	+1.21	−0.85	−1.16
MET-D	**73.61**	**69.66**	**55.44**	**64.43**	**65.79**
Δ	+5.74	+4.04	+2.09	+5.61	+4.37

(b) MCLASH (clr / amb / F1 per language)

	en			es			hi		
Method	clr	amb	F1	clr	amb	F1	clr	amb	F1
Base	**81.96**	**66.38**	**75.99**	51.49	**79.42**	57.71	52.64	**46.95**	49.95
MET	80.00	64.35	74.01	57.85	71.85	60.68	56.35	29.67	47.42
Δ	−1.96	−2.03	−1.98	+6.36	−7.57	+2.97	+3.71	−17.28	−2.53
MET-D	81.60	65.80	75.58	**65.48**	68.28	**64.91**	**57.34**	36.06	**50.13**
Δ	−0.36	−0.58	−0.41	+13.99	−11.14	+7.20	+4.70	−10.89	+0.18

	ko			ms			zh			
Method	clr	amb	F1	clr	amb	F1	clr	amb	F1	avg
Base	**63.24**	**66.99**	**62.82**	33.13	**90.30**	45.54	82.22	52.65	72.17	60.70
MET	61.24	64.52	60.96	40.61	82.78	49.96	85.25	**53.79**	74.71	61.29
Δ	−2.00	−2.47	−1.86	+7.48	−7.52	+4.42	+3.03	+1.14	+2.54	+0.59
MET-D	59.45	66.78	60.11	**54.30**	73.94	**58.48**	**86.60**	51.33	**75.03**	**64.04**
Δ	−3.79	−0.21	−2.71	+21.17	−16.36	+12.94	+4.38	−1.32	+2.86	+3.34

(c) MoCa

Method	Clr	Amb	F1
Base	**52.12**	37.37	43.53
MET	44.17	46.00	42.73
Δ	−7.95	+8.63	−0.80
MET-D	43.58	**50.00**	**44.90**
Δ	−8.54	+12.63	+1.37

Table 6: **Full per-language results (Qwen3-8B)**, in the same format as Table 5. **Bold**/underline mark the best/second-best per column. Δ rows show the difference from Base.

(a) MMoralExceptQA (macro F1 per language)

Method	en	es	hi	zh	avg
Base	**66.56**	65.36	51.89	61.95	61.27
MET	65.27	65.89	52.33	66.44	61.16
Δ	−1.29	+0.53	+0.44	+4.49	−0.11
MET-D	65.51	**69.85**	**57.90**	**70.36**	**64.42**
Δ	−1.05	+4.49	+6.01	+8.41	+3.15

(b) MCLASH (clr / amb / F1 per language)

	en			es			hi		
Method	clr	amb	F1	clr	amb	F1	clr	amb	F1
Base	**86.10**	36.28	69.83	79.47	**43.26**	**67.58**	66.25	30.71	53.21
MET	84.56	31.42	66.95	**79.73**	21.94	59.83	66.49	18.57	48.81
Δ	−1.54	−4.86	−2.88	+0.26	−21.32	−7.75	+0.24	−12.14	−4.40
MET-D	84.70	**50.58**	**73.63**	79.38	34.80	64.58	**69.55**	**41.79**	**59.53**
Δ	−1.40	+14.30	+3.80	−0.09	−8.46	−3.00	+3.30	+11.08	+6.32

	ko			ms			zh			
Method	clr	amb	F1	clr	amb	F1	clr	amb	F1	avg
Base	**81.29**	23.90	61.70	48.51	**66.47**	50.66	**83.83**	22.41	62.70	60.95
MET	77.67	19.81	57.45	57.88	41.94	51.07	80.32	18.63	58.53	57.11
Δ	−3.62	−4.09	−4.25	+9.37	−24.53	+0.41	−3.51	−3.78	−4.17	−3.84
MET-D	76.81	**37.42**	**63.96**	**64.88**	46.83	**57.82**	81.06	**43.56**	**68.97**	**64.75**
Δ	−4.48	+13.52	+2.26	+16.37	−19.64	+7.16	−2.77	+21.15	+6.27	+3.80

(c) MoCa

Method	Clr	Amb	F1
Base	55.27	**16.70**	**40.03**
MET	55.18	7.50	33.60
Δ	−0.09	−9.20	−6.43
MET-D	**57.88**	9.77	34.97
Δ	+2.61	−6.93	−5.06

Table 7: **Full per-language results (Gemma3-4B)**, in the same format as Table 5. **Bold**/underline mark the best/second-best per column. Δ rows show the difference from Base.

Your inner reasoning chain should follow the characteristics below.
Characteristics:
{selected grounds}

Figure 16: **Instruction for following the grounds**: This instruction is included in each benchmark's original prompt to make the target model follow the selected grounds. It is translated into the target language using Google Translate to elicit multilingual responses.

I will give you a text, and you should output values that are closely related to this text.

Values are defined as: The intrinsic goods or ideals that people pursue or cherish, such as happiness, well-being, justice, or freedom. Values are the desirable qualities that people may seek in their lives and in the world. They are often the guiding principles for individuals and societies, shaping goals, motivations, and preferences.

Here is the text: {text}
The output format should be like this. You should strictly follow the output format as it will be automatically parsed.:
Reason: {{reason}}
Values: {{value 1}}, {{value 2}}, {{value 3}}, {{value 4}}, ...

Now, present your answer.

Figure 17: **Prompt used for extracting values from WVS questionaire**

Method	Macro F1 (%) / Native Language (%)						Avg	Δ
	en	es	hi	ko	ms	zh		
Base (not enforced)	71.01	65.65	**52.27**	56.68	62.48	55.87	58.59	—
native %	—	*16.74*	*21.00*	*12.78*	*15.96*	***86.78***	*30.65*	
Base	70.73	64.05	45.66	51.24	63.42	57.74	56.42	−2.17
native %	—	*88.39*	*99.33*	*99.21*	*89.35*	*84.90*	*92.24*	
MET-D (not enforced)	**74.57**	65.14	49.19	57.41	63.86	**63.49**	59.82	+1.23
native %	—	*80.19*	*98.76*	*98.61*	*83.67*	*74.13*	*87.07*	
MET-D	73.75	**67.00**	50.45	**57.88**	**65.45**	62.26	**60.61**	**+2.02**
native %	—	***89.49***	***99.39***	***99.24***	***90.73***	*85.05*	***92.78***	

Table 8: **Experiments on enforcing internal reasoning chain language**: All conditions fix the native-language input prompt and native-language model response; only the reasoning chain language varies. Each method occupies two rows: macro F1 (%) on top and the percentage of reasoning chains detected in the native language below (in italics). **Bold** marks the best F1 per column; Δ denotes the change relative to *base (no enforcement)*.

Situation (abridged). Dr. Allworthy, a long-tenured physician, is being asked by his patients about his political opinions on healthcare policy issues (rising malpractice insurance, Medicare changes, candidate positions). He is considering whether to share his political views and tell patients which candidate he believes is best for their interests. **Character A** values empowering patients with political information relevant to their health decisions but also values maintaining professional boundaries and integrity. **Question.** Was sharing political opinions with patients morally acceptable?

Selected grounds (identical for both models, 10 **total). Each color is the legend for its inline highlights below:** Institution-Based Responsibility-Based Agreement-Based Right-Based Virtue Ethics Contractarianism Stakeholder Harm–Benefit Principle-Based Context-Sensitive .

Base model: full reasoning chain *3 / 10 grounds substantively invoked*

[Internal reasoning trace]

Okay, let's tackle this. The user is presenting a moral dilemma involving a doctor, Dr. Allworthy, and a character named Character A. The questions are about whether Character A would find sharing political opinions with patients acceptable and whether that action would cause discomfort.

First, I need to understand Character A's values. The description says they believe in empowering patients with political info relevant to their health decisions. They also value maintaining professional boundaries and integrity. So, their main concerns are patient autonomy and professional boundaries.

For the first question, does Character A think sharing political opinions is acceptable? The answer hinges on whether this aligns with their values. They want to empower patients, so sharing political info that affects their health decisions could be seen as helpful. However, they also need to maintain professional boundaries. But the scenario mentions that the doctor is already engaging in non-medical conversations, so maybe this is an extension of that. The key is whether sharing political opinions is within the bounds of their role. Since they value empowerment, it's likely acceptable. But maybe there's a line between professional and personal opinions. However, the answer is probably "Yes" because they support patient autonomy.

Second question: If the first answer is yes, would they find it discomforting? Well, if they believe in maintaining professional boundaries, they might feel conflicted. But since they value empowering patients, they might not feel uncomfortable. However, the answer might be "No" because they are in favor of sharing, so not doing it would be uncomfortable. Wait, the second question is phrased as: if the previous answer is yes, would they find the action (sharing) discomforting? If the answer is yes, then the second answer is "No" (they wouldn't find it discomforting). But if the first answer is "Yes," then the second answer is "No" because they would not be uncomfortable. Wait, the second question is phrased as: if the first answer is yes, would they find the action (sharing) discomforting? If the first answer is yes, then the answer to the second is "No" because they would not find it uncomfortable. But maybe they do feel some discomfort because of the boundary issue. But the character's values prioritize patient autonomy, so maybe they don't. Therefore, the second answer is "No".

[Final answer]

1. Reason: Character A values empowering patients with information relevant to their health decisions and maintains professional boundaries. Sharing political opinions that may influence healthcare policies aligns with their goal of patient autonomy, provided it does not cross into unprofessional territory. Since the action is framed as sharing relevant political info (not personal opinions), it is acceptable under their values.
Answer: Yes.

2. Reason: Character A prioritizes professional integrity and patient empowerment. While sharing political opinions might involve some boundary-crossing, their commitment to transparency and patient autonomy would likely outweigh any discomfort, making the action mentally or emotionally acceptable.
Answer: No.

MET-D (trained): full reasoning chain *8 / 10 grounds invoked, listed without reconciliation*

[Internal reasoning trace]

Okay, let's tackle this step by step. The user is presenting a moral dilemma involving Dr. Allworthy and Character A. The first question is whether Character A would deem sharing political opinions with patients as acceptable. The second is about whether that action would cause mental or emotional discomfort.

First, I need to understand Character A's values. The description says they believe in empowering patients with political info relevant to their health decisions. They also value maintaining professional boundaries and integrity. So, the key here is balancing patient autonomy with professional boundaries.

For the first question, the action is sharing political opinions. From a normative authority perspective, if there's a social norm that doctors should inform patients about political issues affecting their health, that might be a factor. But the character also emphasizes professional boundaries. So, maybe the answer is ambiguous because it depends on the context. However, the character values empowering patients, so if the info is relevant, it might be acceptable. But if it's crossing into personal opinion, maybe not. The answer might be ambiguous because it's a balance between these factors.

For the second question, if the answer to the first is yes, would they feel discomfort? If they believe in their role to inform patients, they might not feel discomfort. But if they feel they're crossing boundaries, they might. But since the first answer is ambiguous, maybe the second is also ambiguous. Wait, but the user wants the second answer based on the first. So if the first is yes, then the answer to the second is no. If the first is no, then the second is yes. But the first answer is ambiguous. However, the user says the answer for the first is Yes, No, or Ambiguous. So if the first is ambiguous, then the second answer would be based on that. But the user's instructions say that the second answer is Yes or No. Wait, the user says that the answer for the first is Yes, No, or Ambiguous, and the second is Yes or No. So if the first is ambiguous, then the second answer would be based on that. But how?

Alternatively, maybe the first answer is "Yes" because the character believes in empowering patients, so sharing political opinions that are relevant is acceptable. But the professional boundaries might be a concern. However, the character's values prioritize patient autonomy, so maybe the answer is Yes. Then, if they do it, would they feel discomfort? Probably not, because they believe in their role. So the second answer would be No. But if the answer is ambiguous, then the second answer might be Ambiguous. But the user wants the second answer to be Yes or No. So perhaps the first answer is Yes, and the second is No. Let me check the ethical theories again.

Right-based ethics: Does sharing political opinions violate any rights? Probably not, unless it's in a way that's harmful. Virtue ethics: A virtuous person would empower patients, so yes. Contractarianism: If all parties agree that doctors should share relevant info, then yes. So the first answer is Yes. Then, the second question: if they do it, would they feel discomfort? Since they value their role, they might not. So the answer is No. But maybe they feel some discomfort because it's outside their professional role. But the character's values say they believe it's in the patients' best interest, so they might not feel discomfort. So the second answer is No.

[Final answer]

1. Reason: Character A values empowering patients with information relevant to their health decisions and maintains professional boundaries. Sharing political opinions that directly impact healthcare policies aligns with their duty to inform patients, but crossing into personal opinions risks compromising professional integrity. The action is acceptable if the opinions are framed as policy insights rather than personal views, which aligns with normative authority (institutional legitimacy) and virtue ethics (moral excellence). However, ambiguity arises if the line between professional and personal is blurred.
Answer: Ambiguous.

2. Reason: If the action is deemed acceptable (as per the first answer), Character A would likely not feel discomfort, as they prioritize patient autonomy and professional responsibility. However, if the action is perceived as crossing boundaries, they might feel discomfort. Since the first answer is ambiguous, the emotional response depends on the context of how the opinions are shared.
Answer: No.

Figure 18: **Case study without reconciliation** on the English instance `854-ama`. Among the selected ten grounds, the base substantively engages with three (Institution-Based , Virtue Ethics , Context-Sensitive); MET-D engages with eight, adding Right-Based , Contractarianism , Stakeholder , Harm–Benefit , and Principle-Based . Yet broader engagement does not translate into reconciliation. MET-D issues a one-line verdict per framework ("Right-based ethics: … Probably not. Virtue ethics: … so yes. Contractarianism: … then yes."), and concludes yes in its internal trace without explicitly weighing the conflicting verdicts against one another.